

Qualified Vendors List (QVL) Standard table for i

CT5430(P5L13L-X) DDR2 800 Qualified Vendors List (QVL)									
Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	socket support (Opt)
Apacer	75.073AA.G04	DDR2 800	1024MB	SS	APACER	AM4B5808CEWS8E	5		A* B*
Apacer	75.A73AA.G05	DDR2 800	2048MB	DS	APACER	AM4B5808CEWS8E	5		
NANYA	NT1GT64U88D0BY-AD	DDR2 800	1024MB	SS	NANYA	NT5TU128M8DE-AD	5		
NANYA	NT2GT64U88D0BY-AD	DDR2 800	2048MB	DS	NANYA	NT5TU128M8DE-AD	5		

4 Dimm :

- A * : Supports one module inserted in any slot as Single-channel memory configuration
- B * : Supports 2 modules inserted into both the blue or black slots as two pairs of Dual-channel memory configuration

Notice請按此鈕

- When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.
- It is recommended to install the memory modules from the Yellow slots for better overclocking capability.
- The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a higher frequency than the default state.