

Software Release Note

2005/8/3

Introduction: This document describes detailed release information containing firmware version, improvements, known issues and default configuration, etc.

1. Product Information

Model Name: AAM6030VI-B1

2. Version Information

Firmware Version: 2-18-01-0F00.a0_23a

DSL Version: a0_23a

3. File Release Information

File Name:

ASUS_WLAN_NZ_218010F00_fs_kernel

4. Updates

New Features: N/A

Enhancements: N/A

Resolved Bugs:

1. PPPoE/PPPoA Dial on Demand can't automatically tear down.
2. Modem will panic while several PPPoA try fail.
3. DHCP can't show current status

5. Limitations

N/A

6. Known Issues

New Issues: N/A

Old Issues: N/A

Issued By		Reviewed By		Approved By		Rev
ASUS	2005/08/03					1.2

7. Default Configurations

Item		Default configurations
System Information	Login/Password	admin/admin
	Logo	ASUS
	Language (English, Simple Chinese)	English
LAN Setting	LAN IP address/netmask	192.168.1.1/255.255.255.0
	DHCP Server (on/off)	ON
	DHCP pool	192.168.1.2 ~ 192.168.2.254
ADSL Setting	Default mode (Multi, ANSI, G.dmt, G.lit)	Multi
WAN Setting	PVC setting	0/100
	Protocol	PPPoA, user name: admin, password: admin
	Encapsulation	VC/MUX
Router Function	NAT (on/off)	On
	Firewall	On
Management	Telnet (LAN, WAN)	On, Off (not show in Web)
	HTTP (LAN, WAN)	On, Off (not show in Web)
	FTP (LAN, WAN)	N/A
Others	Wireless	Enable, SSID: bcm96345gw channel :11, Country : Worldwide, Security : disable, MAC Restrict Mode: off, Rate :Auto, Basic rate: default, Fragmentation Threshold: 2346, RTS Threshold:2347, DTIM Interval:3, Beacon Interval:100, 54g™ Mode:54g Auto, 54g Protection:Auto
	USB	Bridge

Issued By		Reviewed By		Approved By		Rev
ASUS		2005/08/03				1.2