

Specification

SiS® 730S A7S-VM
MOTHERBOARD

Processor

- Socket A
- AMD® Athlon™/Duron™
550~1200+MHz

Chipset

- SiS® 730S Chipset

FSB

- 266 MHz

Memory

- 2 x DIMM
- Max.1GB PC133 SDRAM

Expansion Slots

- 4 x PCI

VGA

- Chipset Integrated 3D Graphics Accelerator

IDE Ports

- 2 x UltraDMA/100


Audio

- Chipset Integrated PCI H/W Audio

LAN (Optional)

- Realtek® RTL8100 100/10Mbps LAN Controller

AGP-V7700 Series



- Powered by the world's first gigatexel shading GPU - NVIDIA® GeForce2 GTS
- Built-in 32/64 MB DDR video memory with maximum 5.3GB/sec bandwidth - provides best resolution and color depth
- SmartDoctor™ technologies provide the best safety for your valuable system
- VideoSecurity - auto-notification system to monitor environmental deviation

- Digital Timeshifting VCR - Simultaneous TV recording & instant replay with Full-D1 resolution
- Optimized for Direct3D & OpenGL VR features - ensures broad application support
- Stereoscopic video & Picture viewing
- Large screen TV-Out with 800x600 resolution
- ASUS LIVE! Real-time 30 fps 704x480 video capture
- Highly Desired ASUSDVD 2000 software player, Ulead® VideoStudio, and 3D games bundled
- Available models:

- 1). AGP-V7700 DeluxeTV: GeForce2 GTS, 32M DDR SGRAM, TV-out+Video-in, VR-3D glasses, TV-tuner
- 2). AGP-V7700 Deluxe: GeForce2 GTS, 32M DDR SGRAM, TV-out+Video-in, VR-3D glasses
- 3). AGP-V7700 Pure: GeForce2 GTS, 32M DDR SGRAM, 3D glasses upgradable
- 4). AGP-V7700 Pure: GeForce2 GTS, 64M DDR SDRAM, 3D glasses upgradable

Special Features

- Power Loss Recovery, ASUS® JumperFree™, CPU Throttle, STR (Suspend-to-RAM)

Back Panel I/O Ports

- 2 x USB
- 1 x Parallel
- 1 x Serial
- 1 x PS/2 Keyboard
- 1 x PS/2 Mouse
- 1 x Audio I/O
- 1 x Game/MIDI
- 1 x RJ45 (Optional)
- 1 x VGA

Onboard I/O Interface

- 2 Headers to Support 4 USB Ports
- 20-pin ASUS® Panel
- SIR/CIR
- Headphone
- CD/Video/AUX/Modem Audio In
- CPU/Power Supply/Chassis Fan
- ATX Power
- IDE LED
- ASUS® iPanel Connectors

BIOS

- 2Mb,Award® BIOS,PnP,ACPI,SM BIOS2.3,TCAV,
- Green,Boot Block,Symbios® SCSI BIOS

Industrial Standard

- PCI2.2, USB1.1

Manageability

- WfM2.0,DMI2.0,WOL,WOR,Chassis Intrusion,SM Bus

Support CD

- Drivers
- ASUS® PC Probe
- YAMAHA® S-YXG50 Software Wavetable
- Trend® PC-cillin 2000 Anti-Virus Utility
- ASUS® LiveUpdate™ Utility
- Cyberlink® PowerPlayer,PowerDVD Trial,Video Mail

Accessories

- User's Manual
- UltraDMA/100 Cable
- IDE Cable
- Floppy Cable
- 2-Port USB Bracket
- COM2 Port Bracket

Board Size

- microATX Form Factor
- 9.6"x 9.6" (24.4cm x 24.4cm)



The specification is subject to change without notice.
The brand and product names are trademarks of their respective companies.

Copyright© Feb. 2001 ASUSTeK Computer Inc.
150 Li-Te Rd., Peitou, Taipei, Taiwan
<http://www.asus.com/>

15-271046000