

# Specification

**CUA**  
**Game Machine** MOTHERBOARD

## Processor

- Socket 370
- Intel® FCPGA Pentium® III 450~933+MHz
- Intel® PPGA Celeron™ 333~566+MHz

## Chipset

- ALi® ALaddin TNT2 AGPset  
(ALi® M1631 North Bridge and ALi® M1535D South Bridge)
- Integrated NVIDIA TNT2™ 3D/2D Graphics Engine
- Supports UltraDMA/66, 4 USB Ports

## FSB

- 133/100/66 MHz

## Memory

- 3 x DIMM
- Max.1.5GB PC133/PC100 non-ECC SDRAM

## Expansion Slots

- 1 x AMR
- 6 x PCI
- 1 x Video Slot for TV-Out/DFT

## VGA

- Integrated NVIDIA TNT2™ 3D/2D Graphics Engine

## IDE Ports

- 2 x UltraDMA/66/33

## Audio


- AC'97 Compliant 3D Audio
- Crystal® 4299 CODEC

## LAN

- N/A

## SCSI

- N/A



## Special Features

- Power Loss Restart, ASUS® JumperFree™, CPU Throttle,STR (Suspend to RAM)

## Back Panel I/O Ports

- 2 x USB
- 1 x Parallel
- 1 x Serial
- 1 x PS/2 Keyboard
- 1 x PS/2 Mouse
- 1 x Audio I/O
- 1 x Game/MIDI
- 1 x VGA

## Onboard I/O Interface

- 2-USB Headers
- SIR/CIR
- Headphone
- MIC
- CPU/Power Supply/Chassis Fans
- ATX Power
- IDE LED

## BIOS

- 2/4Mb,Award® BIOS,PnP,ACPI,SM BIOS,TCAV(Trend® ChipAway Virus),Green,Boot Block,Symbios® SCSI BIOS

## Industrial Standard

- PCI2.2, USB1.1

## Manageability

- WfM2.0,DMI2.0,WOL,WOR,Chassis Intrusion,SM Bus

## Support CD

- Drivers
- ASUS® PC Probe
- Trend® PC-cillin 98 Anti-Virus Utility
- ASUS® LiveUpdate™ Utility
- Cyberlink® PowerPlayer,PowerDVD Trial,Video Mail
- YAMAHA® S-YXG50 Software Wavetable

## Accessories

- User's Manual
- UltraDMA/66 Cable
- Floppy Cable
- 2-Ports USB Bracket
- 9-pin COM Port Bracket

## Board Size

- ATX Form Factor
- 8.5"x 12" (21.6cm x 30.5cm)



The specification is subject to change without notice.  
The brand and product names are trademarks of their respective companies.

Copyright© Aug. 14, 2000 ASUSTeK Computer Inc.  
150 Li-Te Rd., Peitou, Taipei, Taiwan  
<http://www.asus.com/>

15-271002001