

Specification

CUBX-L
SMART MOTHERBOARD

Processor

- Socket 370
- Intel® FCPGA Pentium® III 450~933+MHz
- Intel® PPGA Celeron™ 333~566+MHz

Chipset

- Intel® 440BX AGPset and PIIX4E South Bridge

FSB

- 66/100 MHz

Memory

- 4 x DIMM
- Max 1GB PC100 ECC SDRAM

Expansion Slots

- 1 x AGP
- 5 x PCI
- 2 x ISA

VGA

- AGP 2x slot

IDE Ports

- Optional UltraDMA/100 Interface

Audio

- N/A


LAN

- N/A

SCSI

- N/A

PCI-1394C



- Provides IEEE 1394 Interface Solution for the Best Quality of Image Processing Peripherals
- Texas Instrument 1394 Controller
- Data Transfer Rate up to 400Mb/s
- 2 External & 1 Internal Connectors Ready for Legacy Free Computer Age
- 32-bit Bus Master PCI Interface Ready
- Low Profile Mechanism for Space Saving Housing
- Bundled with Ulead™ Video Studio DV SE 3.0 Image Software

Special Features

- Power Loss Restart, ASUS® JumperFree™, STR (Suspend to RAM)

Back Panel I/O Ports

- 2 x USB
- 1 x Parallel
- 2 x Serial
- 1 x PS/2 Keyboard
- 1 x PS/2 Mouse

Onboard I/O Interface

- SIR/CIR
- CPU/Power Supply/Chassis Fan
- ATX Power
- IDE LED

BIOS

- 2Mb, Award® BIOS, PnP, ACPI, SM BIOS 2.3, TCAV (Trend® ChipAway Virus), Green, Boot Block, Symbios® SCSI BIOS

Industrial Standard

- PCI2.2, USB1.1

Manageability

- WfM2.0, DMI2.0, WOL, WOR, Chassis Intrusion, SM Bus

Support CD

- Drivers
- Intel® LDCM 6.0
- ASUS® PC Probe
- Trend® PC-cillin 98 Anti-Virus Utility
- ASUS® LiveUpdate Utility
- Cyberlink® PowerPlayer, PowerDVD Trial, Video Mail

Accessories

- User's Manual
- IDE Cable
- Floppy Cable
- Support Driver CD

Board Size

- ATX Form Factor
- 8.6" x 12" (21.9cm x 30.5cm)



The specification is subject to change without notice.
The brand and product names are trademarks of their respective companies.

Copyright© Nov., 2000 ASUSTeK Computer Inc.
150 Li-Te Rd., Peitou, Taipei, Taiwan
<http://www.asus.com/>

15-271016000