

CUBX-L

SMART MOTHERBOARD

- Intel® FCPGA Pentium®III/ Celeron™ Processors
- Intel® 440BX AGPset
- Supports PC100 SDRAM up to 1GB
- Optional UltraDMA/100 IDE Interface
- JumperFree™ CPU Speed Adjust
- PCI 2.2, WfM V2.0 Supported
- Smart BIOS with Internet LiveUpdate
- FCC, CE Certified

440BX AGPset

- ✓ FCPGA CuMine CPU Supported
- ✓ PC100 SDRAM
- ✓ 2 USB Ports
- ✓ Optional UltraDMA/100
- ✓ ASUS® JumperFree™, LiveUpdate™

Flash EEPROM

- 2Mb EEPROM BIOS
- ACPI • Plug and Play
- DMI • Anti Boot Virus
- Green • Symbios SCSI

ASUS® Smart BIOS

- Patented JumperFree Setting for CPU and Vcore Voltage
- Bootup Block Write Protection against Virus Infection
- IDE HD/SCSI HD/MO/ZIP/CD/Floppy Bootup Supported

Super Multi-I/O Chip

- 1xFloppy Port (2.88MB,3 Mode)
- 2xSerial Ports (16550 Fast UART Compatible)
- 1xParallel Port (EPP, ECP Port)
- IrDA TX/RX (SIR)

1x32-bit AGP Bus Slot

PC'99 Color-Coded ATX I/O Connectors

- 1 x PS/2 Keyboard Port
- 1 x PS/2 Mouse Port
- 2 x USB Ports
- 1 x Parallel Port
- 2 x Serial Ports

Socket 370 for Pentium® III/ Celeron™

- Support Intel® Pentium®III 100MHz FSB Processors

Intel® 440BX AGPset

- 100MHz System Bus
- AGP Rev.1.0 Compliant
- Enhanced ACPI

4x DIMM Memory Sockets

- 16MB~1GB PC100 SDRAM

Dual PCI Bus Master IDE Ports Support:

- UltraDMA/33: 33MB/Sec. (Max.)
- PIO Mode 3,4: 17MB/Sec.(Max.)
- DMA Mode 2: 17MB/Sec.(Max.) (The Actual Transfer Speed Depends on HD)
- ATAPI IDE CD-ROM and LS-120 Supported
- Optional Promise® ATA100 IDE Interface

ASUS® PC Health Monitoring


Smart Slots Provide 5P2I Expansion

- PCI 2.2 Specification Compliant

DIP Switch

- Provide Manual Adjustment for CPU and Other Settings

PIIX4E South Bridge



Please Visit ASUS' Web Site: <http://www.asus.com/>



ASUSTeK COMPUTER INC.