

Specification

Solano 2 CUSL2 MOTHERBOARD

Processor

- Socket 370
- Intel® FCPGA Pentium® III 450~933+MHz
- Intel® PPGA Celeron™ 333~566+MHz

Chipset

- Intel® 82815 GMCH
- Intel® 82801 ICH2
- Intel® 82802 AB FWH
- Support 4X AGP, 4 MB AIMM, PC133/PC100 SDRAM, UltraDMA/100

Super I/O & USB Hub

- ITE IT 8703F LPC Chip
- AU9254 USB HUB

FSB

- 66/100/133 MHz

Memory

- 3 x DIMM
- Max.512MB PC133/PC100 non-ECC SDRAM

Expansion Slots

- 1 x AGP Pro/AGP 4X
- 6 x PCI
- 2 x CNR

VGA

- AGP Pro/4X/2X/1X Slot
- Integrated 4X AGP Graphics

IDE Ports

- 2 x UltraDMA/100/66/33

Audio

- N/A

LAN

- N/A

SCSI

- N/A

Special Features

- Power Loss Restart, ASUS® JumperFree™ CPU Throttle, STR (Suspend to RAM), SFS (Stepless Frequency Selection), Vcore & Vio Adjustable

Back Panel I/O Ports

- 2 x USB
- 1 x Parallel
- 1 x Serial
- 1 x PS/2 Keyboard
- 1 x PS/2 Mouse
- 1 X VGA

Onboard I/O Interface

- ASUS® iPanel Connectors
- 3 Headers to Support Optional 5 USB Ports
- 24-pin ASUS® Panel
- SIR/CIR
- CPU/Power Supply/Chassis Fan
- ATX Power
- IDE LED
- COM2
- TV-Out/LCD Module Connectors

BIOS

- 4Mb, Award® BIOS, PnP, ACPI, SM BIOS 2.3, TCAV (Trend® ChipAway Virus), Green, Boot Block, Symbios® SCSI BIOS

Industrial Standard

- PCI2.2, USB1.1

Manageability

- WfM2.0, DMI2.0, WOL, WOR, Chassis Intrusion, SM Bus

Support CD

- Drivers
- Intel® LDCM 6.0
- ASUS® PC Probe
- YAMAHA® S-YXG50 Software Wavetable
- Trend® PC-cillin 98 Anti-Virus Utility
- ASUS® LiveUpdate™ Utility
- Cyberlink® PowerPlayer, PowerDVD Trial, Video Mail

Accessories

- User's Manual
- UltraDMA/66 Cable
- IDE Cable
- Floppy Cable
- 3-Ports USB Bracket

Board Size

- ATX Form Factor
- 8.2"x 12" (20.8cm x 30.5cm)

iPanel Family Easy Connection ! One Touch Management !

- Front Panel Connectivity
 - * 2USB Ports
 - * 1 Serial, 3 Audio Jacks (for iPanel Deluxe model only)
 - * 1 IrDA (optional)
- System Status Detection and Display
 - * Temperatures
 - * Voltage
 - * Startup Diagnostics
 - * System Working Frequency
 - * System Fan Rotation Display
- User-Configurable Hot Keys



The specification is subject to change without notice.
The brand and product names are trademarks of their respective companies.

Copyright© Jan., 2001 ASUSTeK Computer Inc.
150 Li-Te Rd., Peitou, Taipei, Taiwan
<http://www.asus.com/>

15-271001001