

# CUSL2

## SOLANO 2 MOTHERBOARD

- Supports FCPGA Pentium® III/PPGA Celeron™ 133/100/66MHz Front Side Bus Processors
- The Latest Intel® 815E Chipset Design
- ICH2 Supports UltraDMA/100, 4 USB Ports and CNR Slot
- Supports PC133 SDRAM
- CNR Slot Supports Great Flexibility to Use LAN, HPNA, Modem, Audio, USB Adaptors
- Onboard USB Hub Design Supports Max. 7 USB Devices
- Support ASUS® iPanel Basic™ to Provide Easy Connection and One Touch Management
- Stepless Frequency Selection to Explore the System's Limits

### 2 x CNR Slots

- Advanced Communication & Networking Riser
- Support Various LAN/HPNA/Modem/Audio/USB Adaptors

### 6 x 32-bit PCI Slots

- PCI 2.2 Specification Compliant

### AC'97 Compliant 3D Audio (Optional)

- Enhanced 3D Sound

### AGP Pro Slot

- Compatible with AGP Pro/ AGP 4X / AGP 2X Graphics Adaptors

### PC'99 Color Coded ATX I/O Connectors

### Socket 370 for Pentium® III/Celeron™

- Ready for Processors Packaged in FCPGA/PPGA
- Intel® Pentium® III/Celeron™ 133/100/66 MHz FSB Processors

### Intel® GMCH-Graphics Memory Controller Hub

- Supports 133/100/66MHz FSB
- Integrated 4X AGP Graphics, 4MB AIMM VGA Memory Upgradable
- Support AGP 4X Slot
- PC133/PC100 SDRAM

### 3 x DIMM Memory Socket

- Total Memory Capacity 512MB
- PC133/PC100 SDRAM DIMM

### 2 x UltraDMA/100 IDE Connector

- Max 100MB/s Data Transfer Rate

### Intel® ICH2-I/O Controller Hub

- Hosts 32-bit 33MHz Hub Interface & FWH Bus
- UltraDMA/100, 4 USB Ports and CNR Interface

CNR(Communication & Networking Riser)Slot Supports LAN , HPNA, Modem, 6 Channel Audio & USB HUB Adaptors.



AIMM(AGP Inline Memory Module) Can be Installed on AGP Slot to Support 4MB 133MHz SDRAM Display Cache for Integrated Graphics

### ASUS® PC Hardware Monitoring

- CPU / System Temperatures Monitoring
- CPU/System Voltages Monitoring
- Fan Status Detection

### SFS(Stepless Frequency Selection)

- Host Frequency Adjustable by 1 MHz Increment
- Easy Overclocking to Explore the System's Limits

### Intel® FWH-ASUS® Smart BIOS

- JumperFree™ S/W Ease-of-Use Jumper Settings
- Vcore & VIO/CPU/SDRAM Ratio Adjustable
- Bootable from HD/SCSI/MO/ZIP/CD-ROM/Floppy
- ASUS® LiveUpdate™ for Fast BIOS Upgrading
- Award® 4Mb BIOS with H/W RNG for Security



Please Visit ASUS® Web Site: <http://www.asus.com/>

# Intel® 815E

- ✓ 133/100/66MHz FSB
- ✓ PC133/PC100 SDRAM
- ✓ UltraDMA/100 IDE
- ✓ 2 CNR Slots
- ✓ 7 USB Ports
- ✓ ASUS® iPanel Basic™ Support
- ✓ Stepless Frequency Selection



ASUSTeK COMPUTER INC.