

# Specification

CUW(E)-FX  
MAGIC MOTHERBOARD

## Processors

- Supports Socket 370 for Intel® FCPGA Pentium®III/Celeron™ 300-866+MHz

## Chipsets

- CUWE-FX:  
Intel® 810E Chipset with Support for 133/100/66MHz FSB
- CUW-FX:  
Intel® 810 Chipset with Support for 100/66MHz FSB

## System Memory

- 2 DIMM Sockets to Support Max. 512MB PC100 SDRAM

## Expansion Slots

- 1 x PCI Slot + 1 x AMR Slot

## Onboard Audio

- AC'97 Compliant 3D Audio

## LAN(Optional)

- Intel® 82559 100/10 Mbps LAN Controller

## BIOS

- 4Mb Flash ROM, PnP, Award® BIOS, DMI2.0, WfM 2.0, SM BIOS 2.3

## I/O Ports

- 1 x PS/2 Keyboard Port
- 1 x PS/2 Mouse Port
- 2 x USB Ports (4 USB Ports Upgradable)
- 1 x Parallel Port (EPP, ECP), 2 x Serial Ports
- 1 x Game / MIDI Port, Line-in / Out / MIC-In Ports
- 1 x RJ45

## Optional Accessories (Daughter Boards)

- LCD-I: PanelLink LCD Panel Supported
- TVOUT-I: NTSC/PAL TV-Out Supported
- USBHUB: Two Extended USB Ports Supported

## Other Features

- H/W Monitoring, STR, ACPI, ASUS® JumperFree™

## Form Factor

- FlexATX Form Factor: 9.02" x 7.52" (22.9cm x 19.1cm)

## Optional Accessories

LCD (Panel Link)

## Daughter Board

LCD-I Card

P/N:


90-C1T040-00XCN

## Bracket & Cable

DFP Card

P/N:

80-C100F1-01.00



TV-OUT Supported

TVOUT-I Card  
(NTSC & PAL)

P/N:

90-C1T050-00XCN

6-pin Cable

P/N:

14-000000060



AV/S OUT

P/N:

80-C100B5-01



Extra USB Ports

USB HUB Card

P/N:

90-C1T090-00XCN

10-pin Cable

P/N:

14-000000104



2 Ports USB Card

P/N:

80-C100G5-0111

