

# P3C-L

## RAMBUS MOTHERBOARD

- Supports Pentium® III 133MHz Front Side Bus Processors
- Supports PC800 RDRAM for High-end Desktop and Workstation
- AGP4X/AGP Pro Advanced Graphics Slot for 3D Graphics
- Intel® 82559 10/100 Mbps LAN Controller to Support AOL and WOL Features
- UltraDMA/66 IDE Interface
- JumperFree™ CPU Speed Adjust
- PCI 2.2, WfM V2.0 Supported
- Smart BIOS with Internet LiveUpdate™
- NSTL Year 2000 Test Approved

# Intel® 820

## PC800 RDRAM

## AGP4X / AGP Pro Slot

## 133MHz CPU FSB

## UltraDMA/66 IDE

## Intel® 82559 LAN

### Optional ISA Slot

- ISA Slot to Support Legacy Add-on Cards

### YAMAHA® PCI Audio

- YAMAHA® 744 Hardware PCI Audio Controller
- AC'97, PC'98 DirectSound Compliant
- Support 16-bit Full/Half Duplex

### Intel® 82559 10/100 LAN

- 10/100 Mbps Auto-Detection & Negotiation
- Alert-On-LAN & Wake-On-LAN Support

### AMR Slot

- AC'97 Compliant
- Supports Various AMC/AC/MC Adapters

### PC'99 Color-Coded ATX I/O Connectors

- 1 x PS/2 Keyboard Port
- 1 x PS/2 Mouse Port
- 2 x USB Ports
- 1 x RJ45 Port
- 1 x Parallel Port
- 2 x Serial Ports
- 1 x Game Port, 1 x MIC-IN, 1 x Line-Out
- 1 x Line-In(Optional)

### 20-pin ATX Power Supply Connector

### Slot 1 for Pentium® III / II

- Ready for Processors Packaged in SECC/SECC2
- Intel® Pentium® III / II 133MHz / 100 MHz FSB Processor

### Intel® MCH-Memory Controller Hub

- Supports 133MHz FSB
- Supports The Most Advanced RDRAM Memory
- Provides AGP 4X / AGP Pro Graphics Interface

### 2 x RIMM Memory Sockets

- Total Memory Capacity from 64MB to 1GB
- Design for PC800/PC700/PC600 RDRAM

### Intel® ICH-I/O Controller Hub

- Hosts 32-bit 33MHz Hub Interface & FWH Bus
- 5 PCI Masters, UltraDMA/66, AC'97 Interface

### Intel® FWH-ASUS Smart BIOS

- JumperFree™ S/W Ease-of-Use Jumper Settings
- Vcore & CPU/PCI Ratio Adjustable
- Bootable from HD/SCSI/MO/ZIP/CD-ROM/Floppy
- ASUS® LiveUpdate™ for Fast BIOS Upgrading
- Award® 4Mb BIOS with H/W RNG for Security

### ASUS® PC Hardware Monitoring


- CPU / System Voltages / Temperatures Monitoring / Fan Status Detection

### AGP Pro Slot

- Compatible with AGP Pro/AGP 4X / AGP 2X Graphics Adapters

### 5 x 32-bit PCI Slots

- PCI 2.2 Specification Compliant



Please Visit ASUS® Web Site: <http://www.asus.com/>



ASUSTeK COMPUTER INC.