

P3C-S

RAMBUS MOTHERBOARD

- Supports Pentium® III 133MHz Front Side Bus Processors
- Supports PC800 RDRAM for High-end Desktop and Workstation
- AGP4X/AGP Pro Advanced Graphics Slot for 3D Graphics
- Adaptec® 7892 Ultra160 SCSI Controller
- UltraDMA/66 IDE Interface
- JumperFree™ CPU Speed Adjust
- PCI 2.2, WfM V2.0 Supported
- Smart BIOS with Internet LiveUpdate™
- NSTL Year 2000 Test Approved

Intel® 820

PC800 RDRAM

AGP4X / AGP Pro Slot

133MHz CPU FSB

UltraDMA/66 IDE

Adaptec® Ultra160 SCSI

Optional ISA Slot

- ISA Slot to Support Legacy Add-on Cards

YAMAHA® PCI Audio

- YAMAHA® 744 Hardware PCI Audio Controller
- AC'97, PC'98 DirectSound Compliant
- Support 16-bit Full/Half Duplex

5 x 32-bit PCI Slots

- PCI 2.2 Specification Compliant

AMR Slot

- AC'97 Compliant
- Supports Various AMC/AC/MC Adapters

PC'99 Color-Coded ATX I/O Connectors

- 1 x PS/2 Keyboard Port
- 1 x PS/2 Mouse Port
- 2 x USB Ports
- 1 x Parallel Port
- 2 x Serial Ports
- 1 x Game Port, 1 x MIC-IN, 1 x Line-Out
- 1 x Line-In(Optional)

20-pin ATX Power Supply Connector

Slot 1 for Pentium® III / II

- Ready for Processors Packaged in SECC/SECC2
- Intel® Pentium® III / II 133MHz / 100 MHz FSB Processors

Intel® MCH-Memory Controller Hub

- Supports 133MHz FSB
- Supports The Most Advanced RDRAM Memory
- Provides AGP 4X / AGP Pro Graphics Interface

2 x RIMM Memory Sockets

- Total Memory Capacity from 64MB to 1GB
- Design for PC800/PC700/PC600 RDRAM

Intel® ICH-I/O Controller Hub

- Hosts 32-bit 33MHz Hub Interface & FWH Bus
- 5 PCI Masters, UltraDMA/66, AC'97 Interface

Intel® FWH-ASUS Smart BIOS

- JumperFree™ S/W Ease-of-Use Jumper Settings
- Vcore & CPU/PCI Ratio Adjustable
- Bootable from HD/SCSI/MO/ZIP/CD-ROM/Floppy
- ASUS® LiveUpdate™ for Fast BIOS Upgrading
- Award® 4Mb BIOS with H/W RNG for Security

ASUS® PC Hardware Monitoring


- CPU / System Voltages / Temperatures Monitoring / Fan Status Detection

AGP Pro Slot

- Compatible with AGP Pro/AGP 4X / AGP 2X Graphics Adapters

Adaptec® 7892 Ultra160 SCSI Controller

- Maximum Transfer Rate up to 160 MB/s



Please Visit ASUS® Web Site: <http://www.asus.com/>



ASUSTeK COMPUTER INC.