

24x Slim ASUS Slim CD-ROM Drive

SCD-2400

▶ A Perfect Marriage of Performance with Low Power Consumption


Plus

PC99 COMPLIANT



Slim Size and Light Weight

If you are looking for a CD-ROM drive that marries performance perfectly with low power consumption, slim size and light weight, look no further than the new ASUS SCD-2400. With the leading edge technology, best value solutions, and customer satisfaction that made ASUS the solution provider of choice, the ASUS SCD-2400 has features that make it stand out from the rest of slim CD-ROM drives in the market, like being able to read CD media (for example, scratched discs) that may be unreadable by other drives.

▶ **Front Panel**



▶ **Rear Panel**



▶ **Specifications**

Specifications	Description						
Model	SCD-2400						
Data Transfer Rate	3600KB/s maximum						
Access Time	95ms (typical)						
O/S Compatibility	Compatible with MS-DOS, Windows 3.1x, Windows NT, Windows 95, Windows 98, Windows 2000, Windows ME						
Disk Formats	CD-DA, CD-ROM, CD-ROM/XA, mixed mode, CD-i/FMV, Video-CD, Photo CD (single and multi-session), CD Plus, CD-Extra, I-Trax CD, bootable CD						
Data Transfer Format	PIO Mode 4, DMA Multi Word Transfer Rate Mode 2, Ultra DMA 33 Transfer Rate Mode 2						
Data Buffer	128KB cache buffer						
Disk Dimension	12cm and 8cm						
Disk Capacity	650MB (mode 1, 12 cm disk)						
Interface	IDE/ATAPI Interface Compliant to SFF 8020 Rev. 2.6						
Environmental Characteristics	<table border="0"> <tr> <td>Temperature</td> <td>Humidity</td> </tr> <tr> <td>Operating : 5°C to 50°C</td> <td>Operating : 8% to 80%</td> </tr> <tr> <td>Storage: -20°C to 60°C</td> <td>Storage: 5% to 95%</td> </tr> </table>	Temperature	Humidity	Operating : 5°C to 50°C	Operating : 8% to 80%	Storage: -20°C to 60°C	Storage: 5% to 95%
Temperature	Humidity						
Operating : 5°C to 50°C	Operating : 8% to 80%						
Storage: -20°C to 60°C	Storage: 5% to 95%						
Mounting Orientation	Horizontal / Vertical (-5° ~ +5°)						
Dimension	128.0 x 12.7 x 129.0 mm						
Weight	180g (net weight)						
Power Requirement	+5 V DC, ±5% tolerance						



ASUSTeK Computer Inc.
 150 Lite Road, Peitou, Taipei, Taiwan, R.O.C.
 Tel: 886-2-2894-3447 Fax: 886-2-2896-7761
<http://www.asus.com.tw>

ASUS Computer International.
 6737 Mowry Ave. Mowry Business Center, Building 2
 Newark, CA 94560, USA FAX: 1-510-608-4555
<http://www.asus.com>

ASUS Computer GmbH.
 Harkorstr. 25, 40880 Ratingen, BRD, Germany
 TEL: 49-2102-9599-0 FAX: 49-2102-9599-11
<http://www.asuscom.de>