

P7P55D DELUXE Memory Qualified Vendors List (QVL)

P7P55D DELUXE DDR3 1600 Qualified Vendors List (QVL)											
Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Lable(Bios)	Voltage	DIMM socket support (Optional)		
									A*	B*	C*
A-DATA	AD31600G001GMU	DDR3 1600	1GB	SS	N/A	Heat-Sink Package	9-9-9-24 (1333-8-8-8-24)	1.65~1.85		●	
A-DATA	AX3U1600GB1G9-AG	DDR3 1600	2GB(2 x 1GB)	SS	N/A	Heat-Sink Package	9-9-9-24 (1333-8-8-8-24)	1.65~1.85		●	
A-DATA	AX3U1600PB1G8-2P	DDR3 1600	2GB(2 x 1GB)	SS	N/A	Heat-Sink Package	8-8-8-24(1333-9-9-9-24)	1.65-1.85	●	●	●
A-DATA	AD31600E001GMU	DDR3 1600	3GB(3 x 1GB)	SS	N/A	Heat-Sink Package	8-8-8-24(1333-9-9-9-24)	1.65-1.85	●	●	●
A-DATA	AX3U1600GB1G9-3G	DDR3 1600	3GB(3 x 1GB)	SS	N/A	Heat-Sink Package	9-9-9-24 (1333-8-8-8-24)	1.65~1.85		●	
A-DATA	AX3U1600PB1G8-3P	DDR3 1600	3GB(3 x 1GB)	SS	N/A	Heat-Sink Package	8-8-8-24(1333-9-9-9-24)	1.65-1.85	●	●	●
A-DATA	AX3U1600XB2G7-EF(XMP)	DDR3 1600	4GB(2 x 2GB)	DS	N/A	Heat-Sink Package	7-7-7-20(1333-9-9-9-24)	1.75-1.85	●	●	●
A-DATA	AD31600F002GMU(XMP)	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	7-7-7-20(1333-9-9-9-24)	1.75-1.85	●	●	●
A-DATA	AX3U1600XB2G7-FF(XMP)	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	7-7-7-20(1333-9-9-9-24)	1.75-1.85	●	●	●
CORSAIR	TR3X3G1600C8D	DDR3 1600	3GB(3 x 1GB)	SS	N/A	Heat-Sink Package	8-8-8-24(1600-8-8-8-24)	1.65	●	●	
CORSAIR	TR3X3G1600C8DVer2.1(XMP)	DDR3 1600	3GB(3 x 1GB)	SS	N/A	Heat-Sink Package	8-8-8-24(1601-8-8-8-24)	1.65	●	●	
CORSAIR	TR3X3G1600C9Ver1.1(XMP)	DDR3 1600	3GB(3 x 1GB)	SS	N/A	Heat-Sink Package	9-9-9-24(1601-9-9-9-24)	1.65	●	●	
CORSAIR	BoxP/N:TW3X4G1600C9DHXNV(CM3X2G1600C9DHXNV)Ver4.1	DDR3 1600	4GB(2 x 2GB)	DS	N/A	Heat-Sink Package	(1333-9-9-9-24)	1.80	●	●	●
CORSAIR	TR3X6G1600C8D	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	8-8-8-24(1600-8-8-8-24)	1.65	●	●	●
CORSAIR	TR3X6G1600C8DVer2.1(XMP)	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	8-8-8-24(1601-8-8-8-24)	1.65	●	●	●
CORSAIR	TR3X6G1600C9Ver2.1(XMP)	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	9-9-9-24(1333-9-9-9-24)	1.65	●	●	●
Crucial	BL12864BA1608.8SFB(XMP)	DDR3 1600	1GB	SS	N/A	Heat-Sink Package	(1601-8-8-8-24)	1.8	●	●	●
G.SKILL	F3-12800CL9D-2GBNQ	DDR3 1600	2GB(2 x 1GB)	SS	N/A	Heat-Sink Package	(1333-9-9-9-24)	1.6	●	●	●
G.SKILL	F3-12800CL9D-4GBRL	DDR3 1600	4GB(2 x 2GB)	SS	N/A	Heat-Sink Package	(1333-9-9-9-24)	1.6	●	●	●
G.SKILL	F3-12800CL9D-4GBNQ	DDR3 1600	4GB(2 x 2GB)	SS	N/A	Heat-Sink Package	(1333-9-9-9-24)	1.6	●	●	●
G.SKILL	F3-12800CL8T-6GBHK(XMP)	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	8-8-8-21(1333-8-8-8-21)	1.6-1.65	●	●	●
G.SKILL	F3-12800CL8T-6GBPI(XMP)	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	8-8-8-21(1066-8-8-8-20)	1.6~1.65	●	●	●
G.SKILL	F3-12800CL9T-6GBNQ	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	9-9-9-24(1601-9-9-9-24)	1.5-1.6	●	●	●
GEIL	GV34GB1600C8DC	DDR3 1600	4GB(2 x 2GB)	DS	N/A	Heat-Sink Package	8-8-8-28(1600-8-8-8-28)	1.6	●	●	●
KINGMAX	FLGD45F-B8K9G-NAES	DDR3 1600	1GB	SS	KINGMAX	KFB8FNGXF-ANX-12A	9(1600-9-8-9-28)	1.5	●	●	●
KINGMAX	FLGE85F-B8K9G-NEES	DDR3 1600	2GB	DS	KINGMAX	KFB8FNGXF-ANX-12A	9(1600-9-8-9-28)	1.5	●	●	●
KINGSTON	KHX12800D3LLK3/GX(XMP)	DDR3 1600	3GB(3 x 1GB)	SS	N/A	Heat-Sink Package	(1600-8-8-8-20)	1.65	●	●	
KINGSTON	KHX1600C9D3K3/12GX(XMP)	DDR3 1600	12GB(3 x 4GB)	DS	N/A	Heat-Sink Package	(1066-7-7-7-20)	1.65	●	●	●
KINGSTON	KHX1600C9D3K2/4G	DDR3 1600	4GB(2 x 2GB)	DS	N/A	Heat-Sink Package	(1333-9-9-9-24)	1.7~1.9	●	●	●
KINGSTON	KHX1600C9D3K3/6GX(XMP)	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	9(1333-9-9-9-24)	1.65	●	●	●
OCZ	OCZ3P1600EB1G	DDR3 1600	1GB	SS	N/A	Heat-Sink Package	7-6-6-24(1333-7-7-7-20)	N/A	●	●	
OCZ	OCZ3G1600LV3GK	DDR3 1600	3GB(3 x 1GB)	SS	N/A	Heat-Sink Package	8-8-8(1066-7-7-7-20)	1.65	●	●	●
OCZ	OCZ3P1600LV3GK	DDR3 1600	3GB(3 x 1GB)	SS	N/A	Heat-Sink Package	7-7-7(1066-7-7-7-20)	1.65	●	●	●
OCZ	OCZ3P1600EB4GK	DDR3 1600	4GB(2 x 2GB)	DS	N/A	Heat-Sink Package	7-7-6(1333-7-7-7-20)	1.8	●	●	●
OCZ	OCZ3X16004GK(XMP)	DDR3 1600	4GB(2 x 2GB)	DS	N/A	Heat-Sink Package	7-7-7(1066-7-7-7-16)	1.9	●	●	●
OCZ	OCZ3FXE1600C7LV6GK	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	7-7-7(1066-9-9-9-24)	1.65	●	●	
OCZ	OCZ3G1600LV6GK	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	8-8-8(1066-7-7-7-20)	1.65	●	●	●
OCZ	OCZ3G1600LV6GK	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	8-8-8(1066-7-7-7-16)	1.65	●	●	
OCZ	OCZ3X1600LV6GK(XMP)	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	8-8-8(1600-8-8-8-24)	1.65	●	●	●
OCZ	OCZ3X1600LV6GK(XMP)	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	8-8-8(1066-7-7-7-16)	1.65	●	●	●
Super Talent	WB160UX6GB(XMP)	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	(1333-8-8-8-24)	N/A	●	●	●
Cell Shock	CS322271	DDR3 1600	2GB(2 x 1GB)	DS	N/A	Heat-Sink Package	7-7-7-14(1066-7-7-7-20)	1.7-1.9	●	●	●
Elixir	M2F2G64CB8HA4N-DG	DDR3 1600	2GB	DS	Elixir	N2CB1G80AN-DG	9(1333-9-9-9-28)	N/A	●	●	●
Mushkin	996657	DDR3 1600	4GB(2 x 2GB)	DS	N/A	Heat-Sink Package	7-7-7-20	N/A	●	●	●
Mushkin	998659(XMP)	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	9-9-9-24(1333-9-9-9-24)	1.5-1.6	●	●	●
Patriot	PVT33G1600ELK	DDR3 1600	3GB(3 x 1GB)	SS	N/A	Heat-Sink Package	9-9-9-24(1066-7-7-7-20)	1.65	●	●	●
Patriot	PVS34G1600ELK	DDR3 1600	4GB(2 x 2GB)	DS	N/A	Heat-Sink Package	9-9-9-24(1066-7-7-7-20)	1.8	●	●	
Patriot	PVS34G1600LLK(XMP)	DDR3 1600	4GB(2 x 2GB)	DS	N/A	Heat-Sink Package	7-7-7-20(1066-7-7-7-20)	1.9	●	●	
Patriot	PVS34G1600LLKN	DDR3 1600	4GB(2 x 2GB)	DS	N/A	Heat-Sink Package	7-7-7-20(1066-7-7-7-20)	2.0	●	●	
Patriot	PVT36G1600ELK	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	9-9-9-24(1066-7-7-7-20)	1.65	●	●	●
Patriot	PVT36G1600ELK	DDR3 1600	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	9-9-9-24(1600-7-7-7-20)	1.65	●	●	●

- 6 Dimm :
- **A\***: Supports [one module](#) inserted in any slot as Single-channel memory configuration
  - **B\***: Supports [one pair of modules](#) inserted into either the blue slots or the black slots as one pair of [Dual-channel](#) memory configuration
  - **C\***: Supports [4 modules](#) inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.  
-It is recommended to install the memory modules from the **Blue** slots for better overclocking capability.  
-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.

P7P55 DELUXE DDR3 1625 Qualified Vendors List (QVL)

Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	DIMM socket support (Optional)		
									A*	B*	C*
KINGSTON	KHX13000D3LLK2/2GN(EPP)	DDR3 1625	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package		1.9	●	●	●
KINGSTON	KHX13000D3LLK2/2GX(XMP)	DDR3 1625	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package		1.9	●	●	●
KINGSTON	KHX13000D3LLK2/2GXN	DDR3 1625	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package		1.9	●	●	

- 4 Dimm :
- **A\***: Supports [one module](#) inserted in any slot as Single-channel memory configuration
  - **B\***: Supports [one pair of modules](#) inserted into either the blue slots or the black slots as one pair of [Dual-channel](#) memory configuration
  - **C\***: Supports [4 modules](#) inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.  
-It is recommended to install the memory modules from the **Blue** slots for better overclocking capability.  
-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.

P7P55 DELUXE DDR3 1800 Qualified Vendors List (QVL)

Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	DIMM socket support (Optional)		
									A*	B*	C*
CORSAIR	BoxP/N:TW3X4G1800C8DF(CM3X2G1800C8D)Ver4.1(XMP)	DDR3 1800	4GB(2 x 2GB)	DS	N/A	Heat-Sink Package	8-8-8-24	1.80	●	●	
KINGSTON	KHX1800C9D3T1K3/6GX(XMP)	DDR3 1800	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	(1333-9-9-9-24)	1.65	●	●	●
OCZ	OCZ3P18002GK	DDR3 1800	2GB(2 x 1GB)	SS	N/A	Heat-Sink Package	8	N/A	●	●	●
OCZ	OCZ3P18004GK	DDR3 1800	4GB(2 x 2GB)	DS	N/A	Heat-Sink Package	8	1.9	●	●	
Transcend	TX1800KLU-2GK(XMP)	DDR3 1800	2GB(2 x 1GB)	SS	N/A	Heat-Sink Package	8	N/A	●	●	
Patriot	PVS32G1800LLKN(EPP)	DDR3 1800	2GB(2 x 1GB)	SS	N/A	Heat-Sink Package	8-8-8-20(1066-7-7-7-20)	1.9		●	●

- 4 Dimm :
- **A\***: Supports [one module](#) inserted in any slot as Single-channel memory configuration
  - **B\***: Supports [one pair of modules](#) inserted into either the blue slots or the black slots as one pair of [Dual-channel](#) memory configuration
  - **C\***: Supports [4 modules](#) inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.  
-It is recommended to install the memory modules from the **Blue** slots for better overclocking capability.  
-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.

P7P55 DELUXE DDR3 1866 Qualified Vendors List (QVL)

Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	DIMM socket support (Optional)		
									A*	B*	C*
CORSAIR	TR3X3G1866C9D(XMP)Ver4.1	DDR3 1866	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	9-9-9-24(1866-9-9-9-24)	1.65	●	●	●
CORSAIR	TR3X6G1866C9D(XMP)Ver4.1	DDR3 1866	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1866-9-9-9-24)	1.65	●	●	●
KINGSTON	KHX14900D3K3/3GX(XMP)	DDR3 1866	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	9(1333-9-9-9-24)	1.65	●	●	●
OCZ	OCZ3RPR1866C9LV3GK	DDR3 1866	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	9-9-9(1066-7-7-7-20)	1.65	●	●	
OCZ	OCZ3P1866C9LV6GK	DDR3 1866	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9(1066-7-7-7-20)	1.65	●	●	●
OCZ	OCZ3RPR1866C9LV6GK	DDR3 1866	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9(1066-7-7-7-20)	1.65	●	●	
Super Talent	W1866UX2GB(XMP)	DDR3 1866	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	8-8-8-24(1333-9-9-9-24)	N/A	●	●	●
Patriot	PVS32G1866LLK(XMP)	DDR3 1866	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	8-8-8-24(1066-7-7-7-20)	1.9		●	
Patriot	PVS32G1866LLK(XMP)	DDR3 1866	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	8-8-8-24(1866-8-8-8-24)	1.9	●	●	●

- 4 Dimm :
- **A\***: Supports [one module](#) inserted in any slot as Single-channel memory configuration
  - **B\***: Supports [one pair of modules](#) inserted into either the blue slots or the black slots as one pair of [Dual-channel](#) memory configuration
  - **C\***: Supports [4 modules](#) inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.  
-It is recommended to install the memory modules from the **Blue** slots for better overclocking capability.  
-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.

P7P55 DELUXE DDR3 2000 Qualified Vendors List (QVL)

Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	DIMM socket support (Optional)		
									A*	B*	C*
Crucial	BL12864BE2009.8SFB3(EPP)	DDR3 2000	1GB	SS	N/A	Heat-Sink Package	9-9-9-28(1333-9-9-9-24)	2	•	•	•
G.SKILL	F3-16000CL7T-6GBPS(XMP)	DDR3 2000	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	7-8-7-20(1066-8-8-8-20)	1.65	•	•	
G.SKILL	F3-16000CL9T-6GBPS(XMP)	DDR3 2000	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	9-9-9-24(1066-8-8-8-20)	1.65	•	•	
KINGSTON	KHX2000C9D3T1K3/3GX(XMP)	DDR3 2000	3GB(3 x 1GB)	SS	N/A	Heat-Sink Package	9 (1333-8-8-8-24)	1.65	•	•	•
KINGSTON	KHX2000C8D3T1K3/3GX(XMP)	DDR3 2000	3GB(3x1GB)	SS	N/A	Heat-Sink Package	8(1333-9-9-9-24)	1.65	•	•	•
KINGSTON	KHX2000C9D3T1K3/6GX(XMP)	DDR3 2000	6GB(3 x 1GB)	DS	N/A	Heat-Sink Package	9 (1333-9-9-9-24)	1.65	•	•	•
KINGSTON	KHX2000C8D3T1K3/6GX(XMP)	DDR3 2000	6GB(3x2GB)	DS	N/A	Heat-Sink Package	8(1333-9-9-9-21)	1.65	•	•	•
OCZ	OCZ3FT20002GK	DDR3 2000	2GB(2 x 1GB)	SS	N/A	Heat-Sink Package	8	1.9	•	•	
OCZ	OCZ3P20002GK(EPP)	DDR3 2000	2GB(2 x 1GB)	SS	N/A	Heat-Sink Package	9	1.9	•	•	
OCZ	OCZ3P2000EB2GK	DDR3 2000	2GB(2 x 1GB)	SS	N/A	Heat-Sink Package	9-8-8(1066-8-7-7-20)	1.8	•	•	•
OCZ	OCZ3B2000LV6GK	DDR3 2000	6GB(3 x 2GB)	DS	N/A	Heat-Sink Package	7-8-7(1066-9-9-9-24)	1.65	•	•	
Gingie	9CAASS37AZZ01D1	DDR3 2000	2GB	DS	N/A	Heat-Sink Package	9-9-9-24	N/A	•	•	•
Patriot	PVS32G2000LLKN	DDR3 2000	2GB(2 x 1GB)	SS	N/A	Heat-Sink Package	9-9-9-24(1066-7-7-7-20)	2	•	•	