

Qualified Vendors List (QVL) Standard table for user manual

Project Name : P6T Deluxe 1.02G BIOS : 307

Vendor	Part No.	Size	SS/DS	Chip No.	CL	Chip Brand	DIMM socket support (Optional)			
							A*	B*	C*	D*
CORSAIR	Box P/N:TWIN3X2048-1600C7DHXIN (CM3X1024-1600C7DHXIN)(XMP)	DDR3 1600 2048MB(Kit of 2)	SS	Heat-Sink Package	7	N/A	V	V		
CORSAIR	BoxP/N:TW3X4G1600C9DHXNV(CM3X2 G1600C9DHXNV)	DDR3 1600 4096MB(Kit of 2)	DS	Heat-Sink Package	9-9-9-24	N/A	V	V		V
CORSAIR	BoxP/N:TWIN3X4096-1600C7DHXIN (CM3X2048-1600C7DHXIN)	DDR3 1600 4096MB(Kit of 2)	DS	Heat-Sink Package	N/A	N/A	V	V		
Crucial	BL12864BA1608.8SFB(XMP)	DDR3 1600 1024MB	SS	Heat-Sink Package	N/A	PQI	V	V		V
G.SKILL	F3-12800CL7D-2GBHZ	DDR3 1600 2048MB(Kit of 2)	SS	Heat-Sink Package	7-7-7-18	N/A	V	V		
G.SKILL	F3-12800CL7D-4GBPI	DDR3 1600 4096MB(Kit of 2)	DS	Heat-Sink Package	7-7-7-18	N/A	V	V		
Kingston	KHX12800D3K2/4G	DDR3 1600 4096MB(Kit of 2)	SS	Heat-Sink Package	N/A	N/A		V		V
OCZ	OCZ3P16002GK	DDR3 1600 2048MB(Kit of 2)	SS	Heat-Sink Package	7	N/A	V			
OCZ	OCZ3P1600EB1G(XMP)	DDR3 1600 1024MB	SS	Heat-Sink Package	N/A	N/A	V			
OCZ	OCZ3T1600XM2GK	DDR3 1600 1024MB	SS	Heat-Sink Package	N/A	N/A	V	V		
OCZ	OCZ3P1600EB4GK	DDR3 1600 4096MB(Kit of 2)	DS	Heat-Sink Package	776	N/A	V	V		
OCZ	OCZ3RPR16004GK	DDR3 1600 4096MB(Kit of 2)	DS	Heat-Sink Package	7	N/A				
Aeneon	AXH760UD10-16H	DDR3 1600 1024MB	SS	Heat-Sink Package	9	N/A	V	V		V
Aeneon	AXH860UD20-16H	DDR3 1600 2048MB	DS	Heat-Sink Package	9	N/A	V	V		V
Patriot	PVS34G1600LLKN	DDR3 1600 4096MB(Kit of 2)	DS	Heat-Sink Package	7-7-7-20	N/A	V	V		
PQI	MFADR322LA0101-08A3	DDR3 1600 1024MB	DS	PQD3648S12R	N/A	PQI				
Team	BoxP/N:TXD32048M1600HC7DC (TXD31024M1600HC7)	DDR3 1600 2048MB(Kit of 2)	SS	Heat-Sink Package	7-7-7-21	N/A	V	V		V

Side(s): SS - Single-sided DS - Double-sided

DIMM support:

- **A***: Supports two (2) modules inserted into slot A1 and B1 as one pair of Dual-channel memory configuration
- **B***: Supports three (3) modules inserted into the orange slots (A1, B1 and C1) as one set of Triple-channel memory configuration
- **C***: Supports four (4) modules inserted into the orange slots (A1, B1 and C1) and the black slot A2 as one set of Triple-channel memory configuration
- **D***: Supports six (6) modules inserted into both the orange slots and the black slots as two set of Triple-channel memory configuration.