

RAMPAGE II GENE Memory Qualified Vendors List (QVL)							PM COPY					
RAMPAGE II GENE DDR3 1600 Qualified Vendors List (QVL)												
Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	DIMM socket support (Optional)			
									A*	B*	C*	D*
A-DATA	AD31600E001GMU	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	8-8-8-24(1333-9-9-9-24)	1.65-1.85	●	●	●	●
A-DATA	AD31600F002GMU(XMP)	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	7-7-7-20(1333-9-9-9-24)	1.75-1.85	●	●	●	●
CORSAIR	BoxP/N:TWIN3X2048-1600C7DHXIN (CM3X1024-1600C7DHXIN)(XMP)Ver3.1	DDR3 1600	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	7-7-7-20(1333-9-9-9-24)	1.80	●	●	●	●
CORSAIR	TR3X3G1600C8D(XMP)Ver2.1	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	8-8-8-24(1601-8-8-8-24)	1.65	●	●		
CORSAIR	TR3X3G1600C8D	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	8-8-8-24(1600-8-8-8-24)	1.65	●	●		
CORSAIR	TR3X3G1600C9(XMP)Ver1.1	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	9-9-9-24(1601-9-9-9-24)	1.65	●	●		
CORSAIR	BoxP/N:TW3X4G1600C9DHXNV (CM3X2G1600C9DHXNV)Ver4.1	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	(1333-9-9--9-24)	1.80	●	●	●	
CORSAIR	BoxP/N:TWIN3X4096-1600C7DHXIN (CM3X2048-1600C7DHXIN)Ver3.1	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	(1601-7-7-7-20)	1.90	●	●	●	
CORSAIR	TR3X6G1600C8D(XMP)Ver2.1	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8-24(1601-8-8-8-24)	1.65	●	●	●	
CORSAIR	TR3X6G1600C8D	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8-24(1600-8-8-8-24)	1.65	●	●		●
CORSAIR	TR3X6G1600C9(XMP)Ver2.1	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1333-9-9-9-24)	1.65	●	●	●	
Crucial	BL12864BA1608.8SFB(XMP)	DDR3 1600	1024MB	SS	N/A	Heat-Sink Package	(1601-8-8-8-24)	1.8	●	●	●	●
G.SKILL	F3-12800CL7D-2GBHZ	DDR3 1600	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	(1601-7-7-7-18)	1.9	●	●	●	●
G.SKILL	F3-12800CL9D-2GBNQ	DDR3 1600	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	(1333-9-9-9-24)	1.6	●	●	●	●
G.SKILL	F3-12800CL7D-4GBPI	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-7-18(1333-9-9-9-24)	1.9	●			
G.Skill	F3-12800CL8T-6GBHK(XMP)	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8-21(1333-8-8-8-21)	1.6-1.65	●	●	●	●
G.SKILL	F3-12800CL9T-6GBNQ	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1601-9-9-9-24)	1.5-1.6	●	●	●	●
KINGMAX	FLGD45F-B8KG9-NAES	DDR3 1600	1024MB	SS	KINGMAX	KFB8FNGXF-ANX-12A	9(1600-9-8-9-28)	1.5	●	●	●	●
KINGMAX	FLGE85F-B8KG9-NEES	DDR3 1600	2048MB	DS	KINGMAX	KFB8FNGXF-ANX-12A	9(1600-9-8-9-28)	1.5	●	●	●	●
KINGSTON	KHX12800D3LLK3/3GX(XMP)	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	(1333-9-9-9-24)	1.65	●	●	●	
KINGSTON	KHX12800D3K2/4G	DDR3 1600	4096MB(Kit of 2)	SS	N/A	Heat-Sink Package	(1066-7-7-7-20)	1.9	●	●	●	
KINGSTON	KHX12800D3LLK/6GX(XMP)	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	1600-8-8-8-20	1.65	●	●	●	●
OCZ	OCZ3P1600EB1G	DDR3 1600	1024MB	SS	N/A	Heat-Sink Package	7-6-6-24(1333-7-7-7-20)		●			
OCZ	OCZ3T1600XM2GK(XMP)	DDR3 1600	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	(1601-8-8-8-28)		●	●	●	●
OCZ	OCZ3G1600LV3GK	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	8-8-8(1066-7-7-7-20)	1.65	●	●	●	●
OCZ	OCZ3P1600LV3GK	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	7-7-7(1066-7-7-7-20)	1.65	●	●	●	●
OCZ	OCZ3P16004GK	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-7(1333-7-7-7-20)	1.9			●	
OCZ	OCZ3P1600EB4GK	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-6(1333-7-7-7-20)	1.8	●	●	●	●
OCZ	OCZ3X16004GK	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-7-20	1.9				
OCZ	OCZ3G1600LV6GK	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8(1066-7-7-7-20)	1.65	●	●		
OCZ	OCZ3X1600LV6GK(XMP)	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	8-8-8(1600-8-8-8-24)	1.65	●	●	●	●
Cell Shock	CS322271	DDR3 1600	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-7-14(1066-7-7-7-20)	1.7-1.9	●	●	●	
Elixir	M2F2G64CB8HA4N-DG	DDR3 1600	2048MB	DS	Elixir	N2CB1G80AN-DG	9(1333-9-9-9-28)		●	●	●	●
Mushkin	996657	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-7-20		●	●	●	●
Mushkin	998659	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1333-9-9-9-24)	1.5-1.6	●	●	●	
Patriot	PVT33G1600ELK	DDR3 1600	3072MB(Kit of 3)	SS	N/A	Heat-Sink Package	9-9-9-24(1066-7-7-7-20)	1.65	●	●	●	
Patriot	PVS34G1600ELK	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	9-9-9-24(1066-7-7-7-20)	1.8	●	●		
Patriot	PVS34G1600LLK	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-7-20(1066-7-7-7-20)	1.9	●			
Patriot	PVS34G1600LLKN	DDR3 1600	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	7-7-7-20(1066-7-7-7-20)	2.0	●	●	●	●
Patriot	PVT36G1600ELK	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1066-7-7-7-20)	1.65	●	●	●	●
Patriot	PVT36G1600ELK	DDR3 1600	6144MB(Kit of 3)	DS	N/A	Heat-Sink Package	9-9-9-24(1600-7-7-7-20)	1.65	●	●	●	●

- 6 Dimm :
- **A***: Supports **two (2) modules** inserted into slot A1 and B1 as one pair of Dual-channel memory configuration
 - **B***: Supports **three (3) modules** inserted into the orange slots (A1, B1 and C1) as one set of Triple-channel memory configuration
 - **C***: Supports **four (4) modules** inserted into the orange slots (A1, B1 and C1) and the black slot A2 as one set of Triple-channel memory configuration
 - **D***: Supports **six (6) modules** inserted into both the orange slots and the black slots as two set of Triple-channel memory configuration.

Note請按此鈕

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.