

Qualified Vendors List (QVL) Standard table for user manual

Project Name : P6T WS PRO BIOS : O202

Vendor	Part No.	Size	SS/DS	Chip No.	CL	Chip Brand	DIMM socket support (Optional)			D*	Test Information	
							A*	B*	C*		CL	Voltage
A-DATA	SC631B16	DDR3 1333 2048MB	DS	K4 B1G0846D	9	SAMSUNG	V	V	V	V	Auto	Auto
CORSAIR	Box P/N:TW3X4G1333C9DHX (CM3X2048-1333C9DHX)	DDR3 1333 4096MB(K1 of 2)	DS	Heat-Sink Package	9-9-9-24	N/A	V	V	V	V	Auto	Auto
CORSAIR	Box P/N:TWIN3X2048-1333C9CM3X1024-1333C9)	DDR3 1333 2048MB(K1 of 2)	DS	Heat-Sink Package	9-9-9-24	N/A	V	V	V	V	Auto	Auto
CORSAIR	CM3X1024-1333C9DHX	DDR3 1333 1024MB	DS	Heat-Sink Package	9	N/A	V	V	V	V	Auto	Auto
crucial	CT12864BA1339.8SFB	DDR3 1333 1024MB	SS	D9GTS	9	MICRON	V	V	V	V	0	0
crucial	CT25664BA1339.16SPD	DDR3 1333 2048MB	DS	D9JNM	9	MICRON	V	V	V	V	0	0
ELPIDA	EB11UD8BAFA-DG-E	DDR3 1333 1024MB	DS	J5308BASE-DG-E	8	ELPIDA	V	V	V	V	Auto	Auto
ELPIDA	EB11UD8BAFA-DI-E	DDR3 1333 1024MB	DS	J5308BASE-DI-E	9	ELPIDA	V	V	V	V	Auto	Auto
G.SKILL	F3-10600CL7D-2GBPI	DDR3 1333 2048MB(K1 of 2)	SS	Heat-Sink Package	7-7-7-18	N/A	V	V	V	V	Auto	Auto
G.SKILL	F3-10600CL8D-2GBHK	DDR3 1333 2048MB(K1 of 2)	SS	Heat-Sink Package	8-8-8-21	N/A	V	V	V	V	Auto	Auto
G.SKILL	F3-10600CL9D-2GBPK	DDR3 1333 2048MB(K1 of 2)	SS	Heat-Sink Package	9-9-9-24	N/A	V	V	V	V	Auto	Auto
G.SKILL	F3-10600CL9D-2GBNQ	DDR3 1333 2048MB(K1 of 2)	DS	Heat-Sink Package	9-9-9-24	N/A	V	V	V	V	Auto	Auto
G.SKILL	F3-10666CL9D-4GBPK	DDR3 1333 4096MB(K1 of 2)	DS	Heat-Sink Package	9-9-9-24	N/A	V	V	V	V	Auto	Auto
KINGMAX	FLFD45F-B8EE9	DDR3 1333 1024MB	SS	J1108BASE-DI-E	N/A	ELPIDA	V	V	V	V	Auto	Auto
Kingston	KVR1333D3N9/1G	DDR3 1333 1024MB	SS	J1108BASE-DI-E	N/A	ELPIDA	V	V	V	V	Auto	Auto
Kingston	KVR1333D3N9/2G	DDR3 1333 2048MB	DS	J1108BASE-DI-E	N/A	ELPIDA	V	V	V	V	0	0
MICRON	MT8JTF12864AY-1G4 BYES	DDR3 1333 1024MB	SS	Z9HWR	9	MICRON	V	V	V	V	Auto	Auto
MICRON	MT16TF25664AY-1G4 BYES	DDR3 1333 2048MB	DS	Z9HWR	9	MICRON	V	V	V	V	Auto	Auto
OCZ	OCZ3RPX1333EB2GK	DDR3 1333 1024MB	SS	Heat-Sink Package	6-5-5	N/A	V	V	V	V	Auto	Auto
OCZ	OCZ3G13334GK	DDR3 1333 4096MB(K1 of 2)	DS	Heat-Sink Package	9	N/A	V	V	V	V	Auto	Auto
OCZ	OCZ3P13332GK	DDR3 1333 1024MB	DS	Heat-Sink Package	7-7-7-20	N/A	V	V	V	V	0	0
OCZ	OCZ3P13334GK	DDR3 1333 4096MB(K1 of 2)	DS	Heat-Sink Package	7	N/A	V	V	V	V	Auto	Auto
OCZ	OCZ3RPX1333EB1GK	DDR3 1333 4096MB(K1 of 2)	DS	Heat-Sink Package	6.5.5	N/A	V	V	V	V	Auto	Auto
Qimonda	IMSH1GU03A1F1C-13H	DDR3 1333 1024MB	SS	IDSH1G-03A1F1C-13H	N/A	N/A	V	V	V	V	Auto	Auto
Qimonda	IMSH2GU13A1F1C-13H	DDR3 1333 2048MB	DS	IDSH1G-03A1F1C-13H	N/A	N/A	V	V	V	V	Auto	Auto
SAMSUNG	M378B2873DZ1-C1H9	DDR3 1333 1024MB	SS	K4 B1G0846D	9	SAMSUNG	V	V	V	V	Auto	Auto
SAMSUNG	M391B2873DZ1-C1H9	DDR3 1333 1024MB	SS	K4 B1G0846D(ECC)	9	SAMSUNG	V	V	V	V	Auto	Auto
SAMSUNG	M378B5673DZ1-C1H9	DDR3 1333 2048MB	DS	K4 B1G0846D	9	SAMSUNG	V	V	V	V	0	0
SAMSUNG	M391B5673DZ1-C1H9	DDR3 1333 2048MB	DS	K4 B1G0846D(ECC)	9	SAMSUNG	V	V	V	V	0	0
Transcend	TS128MLK64V3U	DDR3 1333 1024MB	SS	K4 B1G0846D	9	SAMSUNG	V	V	V	V	0	0
Transcend	TS256MLK64V3U	DDR3 1333 2048MB	DS	K4 B1G0846D	9	SAMSUNG	V	V	V	V	0	0
Aeneon	AEH760UD00-13H	DDR3 1333 1024MB	DS	AEH93R13H	9	AENEON	V	V	V	V	0	0
BUFFALO	FSX1333D3G-1G	DDR3 1333 1024MB	SS	Heat-Sink Package	7-7-7-20	N/A	V	V	V	V	Auto	Auto
BUFFALO	FSX1333D3G-2G	DDR3 1333 2048MB	DS	Heat-Sink Package	7-7-7-20	N/A	V	V	V	V	Auto	Auto
Elitix	M2F2C64CB8HA4N-CG	DDR3 1333 2048MB	DS	N2CB1G80A-N-CG	9	Elitix	V	V	V	V	0	0
Patriot	PDC32G1333LLK	DDR3 1333 1024MB(K1 of 2)	SS	Heat-Sink Package	7	Patriot	V	V	V	V	0	0
Kingston	KHX11000D3ULK2/2G	DDR3 1375 2048MB(K1 of 2)	DS	Heat-Sink Package	N/A	N/A	V	V	V	V	0	0

Note :

<<此種顏色的項目,為相同料號的DIMM

<<此種顏色為市佔最高品牌 KINGSTON, Qimonda, SAMSUNG, Hynix, Micron, CORSAIR, ELPIDA, A-Data, Crucial, Apacer, Kingmax, Transcend, Super Talent, NANYA, PSC, TwinMos, OCZ, G.SKILL, G8IL Modules.

A* : Supports one module inserted in any slot as Single-channel memory configuration

B* : Supports one pair of modules inserted into either the blue slots or the black slots as one pair of Dual-channel memory configuration

C* : Supports 4 modules inserted into both the blue and black slots as two pairs of Dual-channel memory configuration