

MAXIMUS II GENE Memory Qualified Vendors List (QVL)

PM COPY

MAXIMUS II GENE DDR2 1150 Qualified Vendors List (QVL)											
Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	DIMM socket support (Optional)		
									A*	B*	C*
KINGSTON	KHX9200D2/1G	DDR2 1150	1024MB	DS	N/A	Heat-Sink Package			●	●	●
OCZ	OCZ2FX11502GK	DDR2 1150	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package			●	●	
OCZ	OCZ2FXT11504GK	DDR2 1150	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	5	2.10	●	●	

- 4 Dimm :
- **A***: Supports [one module](#) inserted in any slot as Single-channel memory configuration
 - **B***: Supports [one pair of modules](#) inserted into either the blue slots or the black slots as one pair of [Dual-channel](#) memory configuration
 - **C***: Supports [4 modules](#) inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

Note請按此鈕

- When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.
- It is recommended to install the memory modules from the slots for better overclocking capability.
- The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.