

MAXIMUS II GENE Memory Qualified Vendors List (QVL)

PM COPY

MAXIMUS II GENE DDR2 1100 Qualified Vendors List (QVL)											
Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	DIMM socket support (Optional)		
									A*	B*	C*
OCZ	OCZ2G11001G	DDR2 1100	1024MB	DS	N/A	Heat-Sink Package	5-6-6(800-5-5-5-15)	2.1	●		
OCZ	OCZ2G11002GK	DDR2 1100	2048MB(Kit of 2)	DS		Heat-Sink Package			●	●	●

4 Dimm :

- **A***: Supports [one module](#) inserted in any slot as Single-channel memory configuration
- **B***: Supports [one pair of modules](#) inserted into either the blue slots or the black slots as one pair of [Dual-channel](#) memory configuration
- **C***: Supports [4 modules](#) inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

Note請按此鈕

- When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.
- It is recommended to install the memory modules from the slots for better overclocking capability.
- The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.