

MAXIMUS II GENE Memory Qualified Vendors List (QVL)						PM COPY						
MAXIMUS II GENE DDR2 1066 Qualified Vendors List (QVL)												
Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	DIMM socket support (Optional)			
									A*	B*	C*	
Apacer	BoxP/N:CH.02GAF.C0KK2 (78.0AG9S.9KF)	DDR2 1066	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15		●	●	●	
Apacer	BoxP/N:CH.04GAF.F0KK2 (78.AAGAL.9KF)	DDR2 1066	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15		●	●	●	
CORSAIR	BoxP/N:TWIN2X4096-8500C5DF (CM2X2048-8500C5D)(EPP)	DDR2 1066	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15	2.1	●	●		
Crucial	BL12864AA106A.8FE5(EPP)	DDR2 1066	1024MB	SS	N/A	Heat-Sink Package	5-5-5-15	2.0	●	●	●	
CRUCIAL	CT25664AA1067.16FE1	DDR2 1066	2048MB	DS	MICRON	9DE12D9JKH	1066-7-7-7-24		●	●	●	
G.SKILL	F2-8500CL5S-1GBPK	DDR2 1066	1024MB	DS	N/A	Heat-Sink Package	5-5-5-15	2.0-2.1	●	●	●	
G.SKILL	F2-8500CL5D-2GBPK	DDR2 1066	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15	2.0-2.1	●	●	●	
G.SKILL	F2-8500CL5D-4GBPK	DDR2 1066	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15	2.0-2.1	●	●	●	
GEIL	GB22GB8500C5DC	DDR2 1066	2048MB(Kit of 2)	SS	GEIL	GL2L128M88BA25AB	5-5-5-15	2.2-2.4	●	●	●	
GEIL	GE22GB1066C5DC	DDR2 1066	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	5-5-5-15	2.2-2.4	●	●	●	
GEIL	GE24GB1066C5QC	DDR2 1066	4096MB(Kitof4)	SS	N/A	Heat-Sink Package	5-5-5-15	2.2-2.4	●	●	●	
GEIL	GB24GB8500C5DC	DDR2 1066	4096MB(Kit of 2)	DS	GEIL	GL2L128M88BA25AB	5-5-5-15	2.2-2.4	●	●	●	
GEIL	GE24GB1066C5DC	DDR2 1066	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15	2.2-2.4	●	●	●	
GEIL	GX24GB8500C5UDC	DDR2 1066	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15	2.2-2.4	●	●	●	
GEIL	GB24GB8500C5QC	DDR2 1066	4096MB(Kitof4)	DS	GEIL	GL2L128M88BA25AB	5-5-5-15	2.2-2.4	●	●	●	
Hynix	HYMP564U64FP8-G7	DDR2 1066	512MB	SS	HYNIX	HY5PS12821FFP-G7	7		●	●	●	
Hynix	HYMP 512U64FP8-G7	DDR2 1066	1024MB	DS	HYNIX	HY5PS12821FFP-G7	7-7-7-12		●	●	●	
KINGMAX	KLED48F-B8KU6-NGES	DDR2 1066	1024MB	SS	KINGMAX	KKB8FNUXF-DXX-18A	1066-6-6-6-24		●	●	●	
KINGMAX	KLED48F-A8KI5-EPA	DDR2 1066	1024MB	DS	KINGMAX	KKA8FEIBF-HJK-18A			●	●	●	
KINGMAX	KLEE88F-B8KU6-NNAS	DDR2 1066	2048MB	DS	KINGMAX	KKB8FNUXF-DXX-18A	1066-6-6-6-24		●	●	●	
KINGSTON	KHX8500D2/1G	DDR2 1066	1024MB	SS	N/A	Heat-Sink Package	800-5-5-5-18	2.2	●	●	●	
KINGSTON	KHX8500D2K2/1GN(EPP)	DDR2 1066	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	800-5-5-5-18	2.2	●	●	●	
KINGSTON	KHX8500D2K2/2GN(EPP)	DDR2 1066	2048MB(Kit of 2)	SS	N/A	Heat-Sink Package	800-5-5-5-18	2.2	●	●	●	
KINGSTON	KVR1066D2N7/1G	DDR2 1066	1024MB	DS	ELPIDA	E5108AJBG-1J-E	1066-5-5-5-15	1.8	●	●	●	
KINGSTON	KHX8500D2K2/2G	DDR2 1066	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package		2.2	●	●	●	
MICRON	MT8HTF12864AY-1GAE1	DDR2 1066	1024MB	SS	MICRON	D9JKH	7		●	●	●	
MICRON	MT16HTF25664AY-1GAE1	DDR2 1066	2048MB	DS	MICRON	D9JKH	7		●	●	●	
OCZ	OCZ2N10662GK(EPP)	DDR2 1066	2048MB(Kit of 2)	DS		Heat-Sink Package			●	●	●	
OCZ	OCZ2N1066SR2GK(EPP)	DDR2 1066	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package	5	2.10	●	●	●	
OCZ	OCZ2RPR10664GK	DDR2 1066	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	5	2.2	●	●		
OCZ	OCZ2RPR10664GK	DDR2 1066	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5(1066-5-5-5-15)	2.2	●			
SAMSUNG	M378T2953GZ3-CF8	DDR2 1066	1024MB	DS	SAMSUNG	K4T51083QG	7		●	●		
Transcend	TX1066QLU-2GK	DDR2 1066	2048MB(Kit of 2)	SS	ELPIDA	Heat-Sink Package	5		●	●	●	
Transcend	TX1066QLU-4GK	DDR2 1066	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	5		●	●	●	
BUFFALO	FSX1066D2C-1G	DDR2 1066	1024MB	DS	N/A	Heat-Sink Package	5-5-5-15(800-5-5-5-15)		●	●	●	
BUFFALO	FSX1066D2C-K4G	DDR2 1066	2048MB	DS	N/A	Heat-Sink Package	5-5-5-15		●	●	●	
Elixir	M2Y1G64TU8HC4B-BD	DDR2 1066	1024MB	DS	Elixir	N2TU 51280CE-BD	6		●	●	●	
Elixir	M2Y2G64TU8HD5B-BD	DDR2 1066	2048MB	DS	Elixir	N2TU16800E-BD	6(1066-6-6-6-24)		●	●	●	
Kingbox	N/A	DDR2 1066	1024MB	DS	MICRON	7YDI2		1.8	●	●	●	
Mushkin	996535	DDR2 1066	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-4-12		●	●		
Mushkin	996612	DDR2 1066	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15	2.1	●	●	●	
Mushkin	996619	DDR2 1066	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15	2.0-2.1	●	●	●	
Patriot	PVS24G8500ELK	DDR2 1066	4096MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15(1066-5-5-5-15)	2.1	●	●		

- 4 Dimm :
- **A***: Supports [one module](#) inserted in any slot as Single-channel memory configuration
 - **B***: Supports [one pair of modules](#) inserted into either the blue slots or the black slots as one pair of [Dual-channel](#) memory configuration
 - **C***: Supports [4 modules](#) inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

Note請按此鈕

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.