

Qualified Vendors List (QVL) Standard table for user manual

Project Name:

Size	Vendor	Chip No.	CL	Chip Brand	SS/DS	Part No.	DIMM socket support (Optional)		
							A*	B*	C*
DDR2 667 512MB	KINGSTON	D6408TEBGGL3U	5	KINGSTON	SS	KVR667D2N5/512	V	V	V
DDR2 667 1024MB	KINGSTON	D6408TEBGGL3U	5	KINGSTON	DS	KVR667D2N5/1G	V	V	
DDR2 667 256MB	KINGSTON	HYB18T256800AF3S	5	N/A	SS	KVR667D2N5/256	V	V	V
DDR2 667 256MB	KINGSTON	6SB12D9DCG	5	MICRON	SS	KVR667D2N5/256	V	V	V
DDR2 667 2048MB	KINGSTON	E1108AB-6E-E	N/A	ELPIDA	DS	KVR667D2N5/2G	V	V	V
DDR2 667 256MB	Qimonda	HYB18T512160BF-3S	5	INFINEON	SS	HYS64T32000HU-3S-B	V	V	V
DDR2 667 512MB	Qimonda	HYB18T512800BF3S	5	N/A	SS	HYS64T64000HU-3S-B	V	V	V
DDR2 667 1024MB	Qimonda	HYB18T512800BF3S	5	N/A	DS	HYS64T128020HU-3S-B	V	V	V
DDR2 667 512MB	SAMSUNG	ZCE6K4T51083QC	5	SEC	SS	M378T6553CZ0-CE6	V	V	V
DDR2 667 256MB	SAMSUNG	K4T51163QC-ZCE6	5	SAMSUNG	SS	M378T3354CZ3-CE6	V	V	V
DDR2 667 512MB	SAMSUNG	K4T51083QC	5	SEC	SS	M378T6553CZ3-CE6	V	V	V
DDR2 667 1024MB	SAMSUNG	ZCE6K4T51083QC	5	SEC	DS	M378T2953CZ3-CE6	V	V	V
DDR2 667 256MB	SAMSUNG	K4T51163QE-ZCE6	5	SAMSUNG	SS	M378T3354EZ3-CE6	V	V	V
DDR2 667 512MB	SAMSUNG	K4T51083QE	5	SAMSUNG	DS	M378T6553EZS-CE6	V	V	V
DDR2 667 1024MB	SAMSUNG	K4T51083QE	5	SAMSUNG	DS	M378T2953EZ3-CE6	V	V	V
DDR2 667 256MB	Hynix	HY5PS121621CFP-Y5	5	Hynix	SS	HYMP532U64CP6-Y5	V	V	V
DDR2 667 1024MB	Hynix	HY5PS12821CFP-Y5	5	Hynix	DS	HYMP512U64CP8-Y5	V	V	V
DDR2 667 256MB	CORSAIR	MHH00605	N/A	N/A	SS	VS256MB667D2	V	V	V
DDR2 667 512MB	CORSAIR	64M8CFEG	N/A	N/A	SS	VS512MB667D2	V	V	V
DDR2 667 1024MB	CORSAIR	64M8CFEG	N/A	N/A	DS	VS1GB667D2	V	V	V
DDR2 667 256MB	ELPIDA	E2508AB-6E-E	5	ELPIDA	SS	EBE25UC8ABFA-6E-E	V	V	V
DDR2 667 512MB	ELPIDA	E5108AE-6E-E	5	ELPIDA	SS	EBE51UD8AEFA-6E-E	V	V	V
DDR2 667 512MB	A-DATA	AD29608A8A-3EG	5	A-DATA	SS	M2OAD5G3H3166H1C52	V	V	V
DDR2 667 1024MB	A-DATA	AD29608A8A-3EG	5	A-DATA	DS	M2OAD5G3I41761H1C52	V	V	V
DDR2 667 2048MB	A-DATA	NT5TU128M8BJ-3C	N/A	N/A	DS	M2ONY5H3J41701H1C5Z	V	V	V
DDR2 667 512MB	crucial	Heat-Sink Package	3	N/A	SS	BL6464AA663.8FD	V	V	
DDR2 667 1024MB	crucial	Heat-Sink Package	3	N/A	DS	BL12864AA663.16FD	V	V	V
DDR2 667 1024MB	crucial	Heat-Sink Package	3	N/A	DS	BL12864AL664.16FD	V	V	V
DDR2 667 1024MB	crucial	Heat-Sink Package	3	N/A	DS	BL12864AA663.16FD2	V	V	
DDR2 667 512MB	Apacer	AM4B5708GQJS7E0628	5	APACER	SS	AU512E667C5KBGC	V	V	V
DDR2 667 1024MB	Apacer	AM4B5708GQJS7E	5	APACER	DS	AU01GE667C5KBGC	V	V	
DDR2 667 512MB	Transcend	K4T51083QE	N/A	SAMSUNG	SS	TS64MLQ64V6J	V	V	V
DDR2 667 1024MB	Transcend	K4T51083QE	N/A	SAMSUNG	DS	TS128MLQ64V6J	V	V	V
DDR2 667 256MB	Kingmax	N2TU51216AG-3C	5	NANYA	SS	KLCEB68F-36KH5	V	V	V
DDR2 667 512MB	Kingmax	KKEA88B4LAUG-29DX	5	KINGMAX	SS	KLCC28F-A8KB5	V	V	V
DDR2 667 1024MB	Kingmax	KKEA88B4LAUG-29DX	5	KINGMAX	DS	KLCD48F-A8KB5	V	V	
DDR2 667 1024MB	Super Talent	Heat-Sink Package	5	N/A	DS	T6UB1GC5	V	V	V
DDR2 667 512MB	SMART	G64M8XB3ITIX4TUE	5	SMART	SS	TB3D2667C58S	V	V	V
DDR2 667 1024MB	SMART	G64M8XB3ITIX4TUE	5	SMART	DS	TB4D2667C58D	V	V	V
DDR2 667 2048MB	NANYA	NT5TU128M8BJ-3C	5	NANYA	DS	NT2GT64U8HB0JY-3C	V	V	V
DDR2 667 512MB	NANYA	NT5TU64M8BE-3C	5	NANYA	SS	NT512T64U8HB0BY-3C	V	V	V
DDR2 667 512MB	PSC	A3R12E3GEF637BLC5N	5	PSC	SS	AL6E8E63B-6E1K	V	V	V
DDR2 667 1024MB	PSC	A3R12E3GEF637BLC5N	5	PSC	DS	AL7E8E63B-6E1K	V	V	V

Size	Vendor	Chip No.	CL	Chip Brand	SS/DS	Part No.	DIMM socket support (Optional)		
							A*	B*	C*
DDR2 1066 1024MB	CRUCIAL	N/A	5-5-5	N/A	DS	BL12864AA1005	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
DDR2 1066 512MB	CRUCIAL	N/A	5-5-5	N/A	DS	BL6464AA1005	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
DDR2 1066 1024MB	KINGSTON	N/A	5-5-5	N/A	SS	KHX8500D2K2/1GN	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
DDR2 1066 2048MB	KINGSTON	N/A	5-5-5	N/A	DS	KHX8500D2K2/2GN	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
DDR2 1066 1024MB	CORSAIR	N/A	5-5-5	N/A	DS	CM2X1024-8500C5D	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
DDR2 1066 1024MB	CORSAIR	N/A	5-5-5	N/A	DS	CM2X1024-8500	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	

A* : Supports one module inserted in any slot as Single-channel memory configuration

B* : Supports one pair of modules inserted into either the blue slots or the black slots as one pair of Dual-channel memory configuration

C* : Supports 4 modules inserted into both the blue and black slots as two pairs of Dual-channel memory configuration