

P5KPL/EPU(雙面不support四根DIMM) Memory Qualifiec

PM COPY

P5KPL/EPU(雙面不support四根DIMM) DDR2 667 Qualified Vendors List (QVL)												
Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	DIMM socket support (Optional)			
									A*	B*	C*	
A-Data	M2OAD5G314170Q1C58	DDR2 667	1024MB	DS	ADATA	AD29608A8A-3EG80814			●	●		
A-Data	M2OAD5H3J4170I1C53	DDR2 667	2048MB	DS	ADATA	AD20908A8A-3EG 30724			●	●		
Apacer	AM4B5808CQJS7E0749B	DDR2 667	2048MB	DS	Apacer	78.A1G9O.9K4	5		●	●		
Corsair	XMS2-5400	DDR2 667	1024MB	DS	Corsair	Heat-Sink Package	4		●	●		
Kingmax	KLCC28F-A8KB5	DDR2 667	512MB	SS	Kingmax	KKEA88B4LAUG-29DX			●	●	●	
Kingston	KVR667D2N5/2G	DDR2 667	2048MB	DS	ELPIDA	E1108ACBG-8E-E 0813A90CC	5	1.8V	●	●		
PSC	AL6E8E63J-6E1	DDR2 667	1024MB	DS	PSC	A3R12E3JFF717B9A01	5		●	●		
Samsung	M378T5263AZ3-CE6	DDR2 667	4096MB	DS	Samsung	K4T2G084QA-HCE6			●	●		
Super Talent	T667UB1GV	DDR2 667	1024MB	DS	Super Talent	PG 64M8-800 0750	5		●	●		
Vendor	PartNum.	DDRTYPE	Size	SS/DS	Chip Brand	ChipNum.	Timing - Dimm(Bios)	Vol.				

- 4 Dimm :
- **A***: Supports [one module](#) inserted in any slot as Single-channel memory configuration
 - **B***: Supports [one pair of modules](#) inserted into either the blue slots or the black slots as one pair of [Dual-channel](#) memory configuration
 - **C***: Supports [4 modules](#) inserted into both the blue and black slots as two pairs of Dual-channel memory configuration

Note請按此鈕

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.