

P5LD2-V Series Motherboard Qualified Vendors List (QVL)

DDR2 667 QVL for ASUS P5LD2-V Series Motherboards

Size	Vendor	Model	CL	Brand	SS/DS	Component	DIMM socket support (Optional)		
							A*	B*	C*
512MB	CORSAIR	CM2X512-5400C4PRO	4	N/A	DS	N/A	V	V	
512MB	CORSAIR	CM2X512A-5400UL	4	N/A	SS	N/A	V	V	V
256MB	SAMSUNG	M378T3354CZ0-CE6	N/A	SAMSUNG	SS	K4T51163QC-ZCE6	V	V	V
512MB	SAMSUNG	M378T6553CZ0-CE6	N/A	SAMSUNG	DS	K4T51083QC-ZCE6	V	V	V
1024MB	SAMSUNG	M378T2953CZ0-CE6	N/A	SAMSUNG	DS	K4T51083QC-ZCE6	V	V	V
1024MB	Kingston	KVR667D2N5/1G	N/A	Kingston	DS	E5108AE-GE-E	V	V	V
512MB	Kingston	KVR667D2N5/512	N/A	Kingston	SS	E5108AE-GE-E	V	V	V
512MB	Hynix	HYMP564U64AP8-Y5	N/A	Hynix	SS	HY5PS12821AFP-Y5	V	V	V
1024MB	Hynix	HYMP512U64AP8-Y5	N/A	Hynix	DS	HY5PS12821AFP-Y5	V	V	V
1024MB	Hynix	HYMP512U64AP8-Y4	N/A	Hynix	DS	HY5PS12821AFP-Y4	V	V	V
512MB	Hynix	HYMP564U64AP8-Y4	3	Hynix	SS	HY5PS12821AFP-Y4	V	V	V
512MB	MICRON	MT16HTF6464AY-667B4	5	MICRON	DS	4VB41D9CZM	V	V	V
256MB	MICRON	MT8HTF3264AY-667B5	5	MICRON	SS	4SB42D9CZM	V	V	
256MB	MICRON	MT8HTF3264AY-667B6	5	MICRON	SS	5FB42D9DPN	V	V	V
256MB	Infineon	HYS64T32000HU-3S-A	5	Infineon	SS	HYB18T512160AF-3S	V	V	V
512MB	Infineon	HYS64T64000HU-3S-A	5	Infineon	SS	HYB18T512800AF3S	V	V	V
1024MB	Infineon	HYS64T128020HU-3S-A	5	Infineon	DS	HYB18T512800AF3S	V	V	V
512MB	ELPIDA	EBE51UD8AEFA-6E-E	N/A	ELPIDA	SS	E5108AE-GE-E	V	V	V
1024MB	ELPIDA	EBE11UD8AEFA-6E-E	N/A	N/A	DS	N/A	V	V	V
256MB	ELPIDA	EBE25UC8ABFA-6E-E	5	ELPIDA	SS	E2508AB-GE-E	V	V	V
512MB	crucial	BL6464AA664.16FB	4	Ballistix	DS	N/A	V		V
1024MB	crucial	BL12864AA664.16FA	4	N/A	DS	N/A	V	V	V
512MB	crucial	BL6464AA664.16FB	4	N/A	DS	N/A	V	V	
1024MB	crucial	BL12864AL664.16FA	N/A	N/A	DS	N/A	V	V	
512MB	GEIL	GX21GB5300UDC	3	N/A	SS	N/A	V	V	
256MB	NANYA	NT256T64UH4A0FY-3C	5	NANYA	SS	NT5TU32M16AG-3C	V	V	V
512MB	NANYA	NT512T64U88A0BY-3C	5	NANYA	SS	NT5TU64M8AE-3C	V	V	V
512MB	TwinMOS	8G-25JK5-EBT	5	N/A	SS	E5108AE-GE-E	V		V
1024MB	OCZ	OCZ26672048EBDCPE-K	N/A	N/A	DS	N/A	V	V	V
512MB	OCZ	OCZ26671024EBDCPE-K	N/A	N/A	SS	N/A	V	V	V
512MB	KINGMAX	KLCC28F-A8EB5	N/A	ELPIDA	SS	E5108AE-6E-E	V	V	V
512MB	WINTEC	39127282	N/A	N/A	SS	4UAI2D9CRZ		V	V
1024MB	WINTEC	39137282	N/A	N/A	DS	4WAIID9CWX	V	V	V

DDR2 533 QVL for ASUS P5LD2-V Series Motherboards

Size	Vendor	Model	CL	Brand	SS/DS	Component	DIMM socket support (Optional)		
							A*	B*	C*
512MB	SAMSUNG	M378T6553BG0-CD5	N/A	N/A	SS	K4T51083QB-GCD5	V	V	V
1024MB	SAMSUNG	M378T2953BG0-CD5	4	N/A	DS	K4T51083QB-GCD5	V	V	
256MB	SAMSUNG	M378T3253FG0-CD5	4	N/A	SS	K4T56083QF-GCD5	V	V	V
512MB	SAMSUNG	M378T6453FG0-CD5	4	N/A	DS	K4T56083QF-GCD5	V	V	V
512MB	Infineon	HYS64T64000GU-3.7-A	4	Infineon	SS	HYB18T512800AC37	V	V	V
256MB	Infineon	HYS64T32000HU-3.7-A	4	Infineon	SS	HYB18T512160AF-37	V	V	V
1024MB	Infineon	HYS64T128020HU-3.7-A	4	Infineon	DS	HYB18T512800AF37		V	V
512MB	Infineon	HYS64T64000HU-3.7-A	N/A	Infineon	SS	HYB18T512800AF37	V	V	V
512MB	Infineon	HYS64T64000HU-3.7-B	N/A	Infineon	SS	HYB18T512800BF37	V	V	V
1024MB	Infineon	HYS64T128020HU-3.7-B	N/A	Infineon	DS	HYB18T512800BF37	V		
512MB	MICRON	MT16HTF6464AG-53EB2	4	MICRON	DS	4FBID9BQM	V	V	V
256MB	MICRON	MT8HTF3264AY-53EB3	4	MICRON	SS	4FBID9CHM	V	V	V
512MB	MICRON	MT16HTF6464AY-53EB2	4	MICRON	DS	4FBID9CHM	V	V	V
256MB	Kingston	KVR533D2N4/256	N/A	ELPIDA	SS	E5116AB-5C-E	V	V	V
512MB	Kingston	KVR533D2N4/512	N/A	N/A	DS	HY5PS56821F-C4	V	V	V
1024MB	Kingston	KVR533D2N4/1G	N/A	N/A	DS	D6408TE7BL-37		V	V
512MB	Hynix	HYMP564U648-C4	4	N/A	SS	HY5PS12821F-C4	V	V	V
1024MB	Hynix	HYMP512U648-C4	4	N/A	DS	HY5PS12821F-C4	V	V	V
1024MB	Hynix	HYMP512U648-C4	4	N/A	DS	HY5PS12821FP-C4		V	
512MB	Hynix	HYMP564U64AP8-C3	3	N/A	SS	HY5PS12821AFP-C3	V	V	V
1024MB	Hynix	HYMP512U64AP8-C3	3	N/A	DS	HY5PS12821AFP-C3	V		V
512MB	ELPIDA	EBE51UD8ABFA-5C	N/A	ELPIDA	DS	E5108AB-5C-E	V	V	
512MB	ELPIDA	EBE51UD8ABFA-5C-E	N/A	ELPIDA	DS	E5108AB-5C-E	V	V	V
1024MB	ELPIDA	EBE11UD8ABFA-5C-E	N/A	ELPIDA	DS	E5108AB-5C-E	V	V	
2048MB	ELPIDA	EBE21EE8AAFA-5C-E	N/A	ELPIDA	DS	E1108AA-5C-E	V	V	
256MB	KINGMAX	KLBB68K-38SP4	N/A	N/A	SS	K4T56083QF-GCD5	V	V	V
1024MB	KINGMAX	KLBD48F-A8EP4	N/A	N/A	DS	E5108AB-5C-E	V	V	
512MB	KINGMAX	KLBC28F-A8EP4	N/A	N/A	SS	E5108AB-5C-E	V	V	V
256MB	KINGMAX	KLBB68F-38KP4	N/A	KINGMAX	SS	KKE388A4IA-37	V		
512MB	KINGMAX	KLBC28F-A8KP4	N/A	KINGMAX	SS	KKEA88A4IA-37	V	V	V
1024MB	KINGMAX	KLBD48F-A8KP4	N/A	KINGMAX	DS	KKEA88A4IA-37	V	V	V
512MB	TwinMOS	8D-22JB5-K2T	N/A	N/A	SS	K4T51083QB-GCD5		V	
512MB	Apacer	78.81067.420	4	N/A	SS	E2508AB-5C-E	V	V	V
256MB	NANYA	NT256T64UH4A0F-37B	4	NANYA	SS	NT5TU32M16AF-37B	V	V	V
512MB	NANYA	NT512T64U88A0F-37B	4	NANYA	SS	NT5TU64M8AF-37B	V		V

1024MB	NANYA	NT1GT64U8HA0F-37B	4	NANYA	DS	NT5TU64M8AF-37B	V	V	
256MB	elixir	M2U25664TUH4A0F-37B	4	N/A	SS	N2TU51216AF-37B	V	V	V
512MB	elixir	M2U51264TU88A0F-37B	4	N/A	SS	N2TU51280AF-37B	V	V	V
256MB	crucial	BL3264AA53V.8FB	3	Ballistix	SS	N/A	V	V	
512MB	crucial	BL6464AA53V.16FB	3	Ballistix	DS	N/A	V	V	
256MB	CENTURY	25V6S8SSD5F4-K43	4	N/A	SS	K4T56083QF-GCD5	V	V	
512MB	CENTURY	25V2H8EL5CB4-J43	4	N/A	SS	E5108AB-5C-E	V	V	V
1024MB	CENTURY	25VOH8EL5C	4	N/A	DS	E5108AB-5C-E	V	V	
256MB	Aeneon	AET560UD00-370A98X	N/A	Aeneon	SS	AET960UD00-37C88X	V	V	
512MB	Aeneon	AET660UD00-370A98X	N/A	Aeneon	SS	AET960UD00-37C88X	V		
512MB	Aeneon	AET660UD00-370A98X	N/A	Aeneon	SS	AET93F370AG0513	V	V	
512MB	Transcend	TS64MLQ64V5J	4	N/A	SS	K4T51083QB-GCD5	V	V	V
1024MB	Transcend	TS128MLQ64V5J	N/A	N/A	DS	K4T51083QB-GCD5	V		
512MB	PQI	MEAB-323LA	N/A	N/A	SS	64MX8D2-E	V	V	V
1024MB	PQI	MEAB-423LA	N/A	N/A	DS	64MX8D2-E	V	V	V
256MB	SmpleTech	M2GSP2F3G3110A9B0E	N/A	N/A	SS	858S032F25A	V	V	V

DDR2 400 QVL for ASUS P5LD2-V Series Motherboards

Size	Vendor	Model	CL	Brand	SS/DS	Component	DIMM socket support (Optional)		
							A*	B*	C*
256MB	NANYA	NT256T64UH4A0F-5A	N/A	N/A	SS	NT5TU32M16AF-5A	V	V	V
512MB	NANYA	NT512T64U88A0F-5A	N/A	N/A	SS	NT5TU64M8AF-5A	V	V	V
1024MB	Aeneon	AET760UD00-500A08X	N/A	N/A	SS	AET03F50C	V	V	
2048MB	Aeneon	AET860UD00-500A08X	N/A	N/A	DS	AET03F50C	V	V	

Notes:

A* : Supports one module inserted in any slot as Single-channel memory configuration

B* : Supports one pair of modules inserted into either the yellow slots or the black slots as one pair of Dual-channel memory configuration

C* : Supports 4 modules inserted into both the yellow and black slots as two pairs of Dual-channel memory configuration