

ASUS® SK8N Technical Updates

SK8N specifications summary (Page xi)

Internal I/O	Floppy disk drive connector Primary/Secondary IDE connectors 2 x Serial ATA connectors RAID ATA connector Internal audio connectors Front panel audio connector 1 x USB 2.0 connector for additional two (2) USB ports CPU/Chassis/Power fan connectors 20-pin/4-pin ATX 12V power connectors CD/AUX connectors S/PDIF out connector IEEE 1394 connector Serial port 2 connector
BIOS features	4Mb Flash EEPROM AMI BIOS with enhanced ACPI, PnP, DMI2.0, Green ASUS EZ Flash, ASUS MyLogo2, Q-Fan, SM BIOS 2.3, Multi-Language BIOS, CrashFree BIOS2
Industry standard	PCI 2.3, USB 2.0/1.1
Manageability	DMI 2.0, WOL by PME, WOR by PME
Power Requirement	ATX power supply (with 4-pin 12V plug)
Form Factor	ATX form factor: 12 in x 9.6 in (30.5 cm x 24.4 cm)
Support CD contents	Device drivers ASUS PC Probe Trend Micro™ PC-cillin 2002 anti-virus software

* Specifications are subject to change without notice.

15-xxxxxxxx