

M4A78-AM Memory Qualified Vendors List (QVL)

PM COPY

M4A78-AM DDR2 1200 Qualified Vendors List (QVL)

Vendor	Part No.	Type	Size	SS/DS	Chip Brand	Chip NO.	Timing Dimm(Bios)	Voltage	socket support (Opt)	
									A*	B*
Apacer	78.0AGA7.9K4	DDR2 1200	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package				
Kingston	KHX96002K2/2G	DDR2 1200	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-15	2.2V	•	•
OCZ	OCZ2FX12002GK	DDR2 1200	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package	5-5-5-18	2.1 - 2.3 V	•	•
Team	TXDD1024M1300HC6	DDR2 1200	2048MB(Kit of 2)	DS	Heat-Sink Package	Heat-Sink Package	6-6-6-18	2.35V~2.45V	•	•
winchip	64A0TMTHE8G17C	DDR2 1200	2048MB(Kit of 2)	DS	N/A	Heat-Sink Package				
Vendor	PartNum.	DDRTYPE	Size	SS/DS	Chip Brand	ChipNum.	Timing - Dimm(Bios)	Vol.		

2 Dimm :

- **A***: Supports [one module](#) inserted in any slot as Single-channel memory configuration
- **B***: Supports [2 modules](#) inserted into both the blue or black slots as two pairs of Dual-channel memory configuration

Note請按此鈕

-When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended.

-It is recommended to install the memory modules from the slots for better overclocking capability.

-The default DIMM frequency depends on its Serial Presence Detect (SPD), which is the standard way of accessing information from a memory module. Under the default state, some memory modules for overclocking may operate at a lower frequency than the vendor-marked value.