

Index

Ç İ

adding
 drive entry, 12-6
 global spare drive, 8-25
 local spare drive, 8-25
altitude
 operating, G-2
AMD 5x86 CPU, 2-2
automatic rebuild, 3-9

Ç Đ

backward compatibility, 2-2
basic operational setup, 4-12
battery back-up, 4-7
baud rate, 4-10
Baud rate, 11-4
beeper
 mute, 7-36, 8-53
bus width, B-1

Ç Ñ

cable specifications
 SCSI, B-1
cache parameters, 3-12, 7-29, 8-42
capacitance, B-1
changing
 assword, 8-54
 password, 7-37
channel
 mode, 7-3
 mode, redefining, 8-30
 SCSI, status, 7-3, 8-5
channel mode
 viewing and redefining, 7-20
check time
 periodic auto-detection of failed drive swap, 3-17
 periodic drive, 3-15
clustering
 Microsoft® Cluster Server, 10-2

- communication parameters, 7-29, 8-41
- configuring RAID
 - flow chart, 6-1
- controller
 - naming, 7-36, 8-52
 - parameters, 8-52
 - reset, 7-38, 8-56
- CPU, 1-1
- current, G-1
- current settings
 - viewing, 8-7

ç Ò

- DA-ACCY-BD daughterboard
 - installation of battery back-up, 4-7
- DA-ACCY-DU2 daughterboard
 - top view, 4-4
- DA-ACCY-DUS daughterboard
 - top view, 4-3
- DA-ACCY-DUW daughterboard
 - top view, 4-3
- data cache, 2-2
- data rebuilding, 2-1
- daughterboard
 - installation of, 4-6
- DC resistance, B-1
- default setting
 - restoring, 7-28, 8-41
- delay skew, B-1
- deleting
 - logical drive, 8-11
 - LUN mappings, 7-13
 - partition of logical drive, 7-7, 8-12
 - SCSI channel ID, 7-21
 - SCSI ID, 8-32
 - slot number, 12-6
 - spare drive, global or local, 7-18, 8-27
- detection
 - idle drive failure, 7-34, 8-47, 8-51
 - of drive hot swap followed by auto rebuild, 7-33, 8-51
- dial-out
 - automatically on initialization, 11-23
 - command, 11-22
 - conditions, 11-21
 - for event notification, 11-18
 - retry count, 11-20, 11-23
 - retry interval, 11-21
 - setting via front panel, 11-22

- setting via terminal emulation, 11-19
- timeout, 11-20, 11-23
- dimensions, G-2
- disconnecting support, 8-40
- disk access delay time, 3-14, 3-15, 7-32, 8-45
- disk array
 - parameters, 3-11, 7-34, 8-48
- drive status
 - SCSI, 7-2, 8-3
- drives
 - SCSI, viewing and editing, 8-23
- drive-side SCSI parameters, 3-13, 7-31, 8-44
- dynamic logical drive expansion, 3-17, 7-10, 8-15

Ç Ö

- event logs
 - viewing and editing, 7-38
- event notification
 - dial-out to pager or terminal, 11-18
- expansion
 - logical drive, 8-15
 - RAID, 3-17

Ç Ö

- fault-bus
 - configuring via RS-232, 12-9
 - enabling error signal inputs, 12-8
 - how to setup, 12-4
 - port, F-2
 - setting error signal inputs to active-high or -low, 12-7
 - testing failure LED's for drive cannisters, 12-8
 - viewing status of error signal inputs, 12-9
- firmware, 1-1, 2-2
 - upgrading, C-1
- flash memory, 1-1, C-1
- flashing
 - all SCSI drives, 3-8
 - selected SCSI drives, 3-8
- format
 - low-level, 7-19, 8-28
- front panel
 - navigation map, A-1

global spare drive, 3-5

adding, 7-17, 8-25

deleting, 8-27

GUI RAID Manager

upgrading firmware with, C-1

via in-band SCSI, 4-18

host channel

setting, 7-20

host LUN

mapping a logical drive to, 8-18

viewing and editing, 7-12, 8-18

host-side SCSI parameters, 7-30, 8-43

hot swap

drive, detection of followed by auto rebuild, 7-33, 8-51

How does it work?

fault-bus, 12-1

In-band SCSI, 4-13

logical drive expansion, 3-17

SAF-TE, 3-16

the RAID controller, 6-2

I/O timeout

SCSI, 3-15

ID

SCSI, deleting, 8-32

identifying drives, 3-7, 7-17, 8-26

idle drive failure detection, 7-34, 8-47

impedance, B-1

in-band SCSI, 4-13

initializing modem, 11-16

input

error signals, 12-2

JBOD

single drive control, 3-2

LCD, 2-2
LCD panel
 the initial screen, 7-1
local spare drive, 3-5
 adding, 7-16, 8-25
 deleting, 8-27
logical drive, 2-1
 assigning a name, 7-8, 8-13
 creating, 7-4, 8-8
 deleting, 7-6, 8-11
 expansion, 7-10, 8-15
 expansion in Windows NT® Server, 3-21
 mapping to a host LUN, 8-18
 mode 1 expansion of, 3-18
 mode 2 expansion of, 3-19
 partitioning, 7-7
 parity check, 7-11, 8-18
 partitioning, 8-11
 rebuilding, 7-9, 8-14
 status, 7-1, 8-2
 verification on rebuild writes, 7-35
 viewing and editing, 7-4
 viewing drive members, 7-6, 8-10
low-level format, 7-19, 8-28
LUN, 2-2
 explained, 6-2
 mappings, viewing and deleting, 7-13, 8-21
 per host SCSI ID, 7-31, 8-43
 viewing and editing, 8-18
 viewing and editing, 7-12

main board
 rear view, 4-2
 top view, 4-2
main menu (terminal), 8-2
management
 drive failure, 3-5
manual rebuild, 3-9
maximum
 queued I/O count, 7-30, 8-43
maximum synchronous transfer clock, 7-27, 8-38
maximum tag count, 3-15, 7-28, 8-40, 8-46, 8-49
maximum transfer width, 7-27, 8-39
Microsoft® Cluster Server, 10-2

- mode 1
 - logical drive expansion, 3-18
- mode 2
 - logical drive expansion, 3-19
- modem
 - initializing, 11-16
 - remote terminal emulation via, 11-8
- motor spin-up
 - SCSI, 7-31, 8-44
- multiple host
 - diagram showing, 10-6
- mute
 - beeper, 7-36, 8-53

Ç Ü

- naming
 - controller, 7-36, 8-52
 - logical drive, 7-8
- navigation keys
 - in terminal emulation, 5-2
 - on front panel, 4-1
- normal drive writes
 - verification on, 7-36
- NRAID
 - disk spanning, 3-2
- null modem, F-2

Ç Ý

- operating temperature, G-1
- optimization
 - for sequential or random I/O, 3-12, 7-30
- outputs
 - drive failure signal, 12-3

Ç Þ

- pager
 - event notification, 11-18
- parameters
 - cache, 3-12, 7-29, 8-42
 - communication, 7-29, 8-41
 - controller, 8-52
 - disk array, 3-11, 7-34, 8-48

- drive-side SCSI, 3-13, 7-31, 8-44
- host-side SCSI, 7-30, 8-43
- parity check, 7-27, 8-39
 - logical drive, 7-11, 8-18
- partition
 - logical drive, deleting, 7-7, 8-12
 - mapping to host LUN, 6-4
 - number of, 2-1
- partitioning
 - logical drive, 7-7, 8-11
- pass-through SCSI commands, 7-13
- Pass-through SCSI commands, 8-22
- password
 - changing, 7-37, 8-54
 - disabling, 8-55
 - setting a new, 8-55
- periodic drive check time, 3-15
- periodic drive swap auto check, 3-17
- peripheral devices
 - parameter reference for various operating systems, 4-15
 - types of, 4-16
- pin assignments, F-1
- power connection, 4-9
- PPP
 - plus telnet for remote administration, 11-3
- primary controller
 - setting SCSI ID/drive channel for, 8-32
- primary ID
 - SCSI channel, setting, 7-22
- propagation delay, B-1

Ç ß

- queued I/O count
 - maximum, 7-30, 8-43
- quick setup, 5-1

Ç à

- RAID
 - advantages, 3-1
 - management, 3-1
 - What are the levels?, 3-1
- RAID (0+1)
 - concurrent rebuild in, 3-10
 - disk striping with mirroring, 3-4
- RAID 0

- disk striping, 3-3
- RAID 1
 - disk mirroring, 3-3
- RAID 3
 - disk striping with dedicated parity disk, 3-4
- RAID 5
 - striping with interspersed parity, 3-5
- random I/O
 - optimization for, 3-12
- read/write test, 7-19, 8-29
- rebuild
 - automatic, 3-9
 - concurrent in RAID (0+1), 3-10
 - logical drive, 7-9, 8-14
 - manual, 3-9
 - priority, 3-11, 8-48
- record of settings, H-1
- redundant controller
 - assigning logical drives to secondary, 9-10
 - automatic configuration of, 9-7
 - cable, F-3
 - example, 9-4
 - explained, 9-1
 - if one fails, 9-12
 - manual configuration of, 9-8
 - port, F-2
 - starting up, 9-9
 - writeback cache, 9-1
- redundant host, 2-2
 - diagram showing, 10-1
- removing
 - empty drive entry, 12-6
- reset
 - controller, 7-38, 8-56
 - SCSI, at power-up, 3-14, 7-32, 8-45
- retry
 - count dial-out, 11-20
 - interval for dial-out, 11-21
- RS-232
 - configuration via front panel, 4-11
 - configuring fault-bus, 12-9
 - connection and setup, 4-10
 - extension cable, F-3
 - port, F-1
 - upgrading firmware via, C-3

- explained, 3-16
- periodic check time, 7-33, 8-47, 8-50
- scanning a new SCSI drive, 7-14, 8-24
- SCSI
 - cable specifications, B-1
 - channel ID, deleting, 7-21
 - channel ID, setting, 7-20
 - channel primary ID, setting, 7-22
 - channel secondary ID, setting, 7-23
 - channel status, 7-3, 8-5
 - channel terminator, 7-24, 8-35
 - channel, explained, 6-2
 - channels, viewing and editing, 8-30
 - commands, pass-through, 7-13, 8-22
 - drive status, 7-2, 8-3
 - drive utilities, 7-18, 8-28
 - drive, scanning a new one, 7-14, 8-24
 - drives, viewing and editing, 7-14, 8-23
 - I/O timeout, 3-15
 - ID, deleting, 8-32
 - ID, explained, 6-2
 - motor spin-up, 3-13, 7-31, 8-44
 - parameters, drive-side, 3-13
 - reset at power up, 3-14, 7-32, 8-45
 - synchronous clock period, D-1
 - target/drive channel, viewing and editing, 7-26
- secondary controller
 - setting SCSI ID/drive channel for, 8-34
- secondary ID
 - SCSI channel, setting, 7-23
- sequential I/O
 - optimization for, 3-12
- serial port
 - connection and setup, 4-10
- SIMM, 4-4
- slot number, 7-26, 8-38
 - assigning to an empty cannister, 12-5
- SNMP
 - diagram showing, 11-1
- spare drive, 3-5
 - adding a global, 7-17
 - adding a local, 7-16
- specifications, G-1
- system information
 - viewing, 7-38

- tag count
 - maximum, 3-15, 7-28, 8-40, 8-46, 8-49
- target/drive channel
 - SCSI, viewing and editing, 7-26
- telnet
 - plus PPP for remote administration, 11-3
- temperature
 - operating, G-1
- terminal emulation
 - remote administration, 11-3
 - terminology, 8-1
- terminator, 4-13
 - channel, G-1
 - SCSI channel, 7-24, 8-35
- throughput, B-1
- timeout
 - for dial-out, 11-20
- transfer clock
 - maximum synchronous, 7-27, 8-38
- transfer rate, B-1
- transfer speed
 - setting, 7-24, 8-35
- transfer width
 - maximum, 7-27, 8-39
 - setting, 7-25, 8-36

Ç ã

- upgrading
 - firmware, C-1
- utilities
 - for SCSI drives, 7-18, 8-28

Ç ä

- verification
 - logical drive rebuild writes, 7-35
 - normal drive writes, 7-36
- verification on writes, 7-35, 8-49
- verify-after-write, 3-11
- viewing
 - drive information, 8-24
 - system information, 8-56
- viewing and editing
 - configuration parameters, 8-41
 - SCSI channels, 8-30
 - SCSI ID/host channel, 8-31

- SCSI target/drive channel, 8-37
- viewing and redefining a channel mode, 7-20
- voltage, G-1
- VT-100
 - connection and setup, 4-10
 - remote administration via telnet, 11-3
 - terminal, 4-10, 5-2

Ç à

- write-back cache
 - enable or disable, 7-29