

ASUS Zero Client Solution

-- Suggested Configuration Table

ASUS Zero Client Solution – Suggested Configuration

Applications		Maximum # of Z5		Remark
		ESC500** (SKU#1)	ESC500** (SKU#2)	
Office		12	14	-Such as MS-Word, MS-Excel, MS-PowerPoint. (note: WMS 2011 only support the MS Office with <u>Volume Licensing</u>) - Professional editing application (e.g. AutoCAD) is not supported.
Web-based	Search Engine/Portal	10	12	- web browsing without video/flash
	Video Stream/Flash	8	10	- web browsing with video/flash, such as Youtube - Maximum resolution of the flash/video: 480p
Multimedia		5	5	- Maximum resolution of the video: 720p

* If the q'ty of the clients exceeds 10 units, the OS of the host server should be upgraded to Windows Multipoint Server 2011 "Premium".

** Please refer to next page for the details of the ESC500 configurations.

*** With Windows Multipoint Server 2011,

1. Use the same type of keyboard and mouse for the host server, both USB or both PS/2.

(Do not use USB KB with PS/2 mouse; nor PS/2 KB with USB mouse.)

2. When the host server is using USB KB/MS, if it is logged in as a multipoint station, then the audio function of the host server requires the USB audio card to support.

ASUS Zero Client Solution – *Suggested Host Server*

	ESC500 SKU#1	ESC500 SKU#2
Operating System	Windows Multipoint Server 2011 Standard / Premium	
Core Logic	Intel® C206 Chipset	Intel® C206 Chipset
CPU	i5-2400 (3.1GHz, 6MB cache, 4 cores)	i7-2600 (3.4GHz, 8MB cache, 4 cores)
Memory	4GB DDR3, 1333MHz	8GB DDR3, 1333 MHz
Storage	2 x 3.5" HDD / 1 x5.25" Optical Device	
Communications	2 x Intel® 82574L GbE LAN	
Dimension	423mm x 190mm x 435mm (HxWxD)	
Net Weight	10.8KG (CPU, Memory & HDD excluded)	