

EAX1600PRO/TD/512M Output Resolution Reference Table

Interface:	Resolution:	Color Quality(bit):	Refresh Rate(MHz):
D-Sub	800*600	16	60,70,72,75,85
D-Sub	800*601	32	60,70
D-Sub	1024*768	16,32	60,70,72,75,85
D-Sub	1152*864	16,32	60,70,75,85
D-Sub	1280*720	16,32	60
D-Sub	1280*768	16,32	60,75,85
D-Sub	1280*960	16,32	60,70,72,75,85
D-Sub	1280*1024	16,32	60,70,75,85
D-Sub	1360*768	16,32	60,70,72,75,85
D-Sub	1440*900	16,32	60,75,85
D-Sub	1600*1200	16,32	60,70,75,85
D-Sub	1680*1050	16,32	60
D-Sub	1792*1344	16,32	60,72,75,85
D-Sub	1800*1440	16,32	60,70,72,75,85
D-Sub	1856*1392	16,32	60,72,75,85
D-Sub	1920*1080	16,32	60,75
D-Sub	1920*1200	16,32	60,75,85
D-Sub	1920*1440	16,32	60,75,85
D-Sub	2048*1536	16,32	60,70,75,85
DVI	800*600	16,32	60,75
DVI	1024*768	16,32	60,75
DVI	1152*864	16,32	60,75
DVI	1280*720	16,32	60
DVI	1280*768	16,32	60,75
DVI	1280*960	16,32	60,75
DVI	1280*1024	16,32	60,75
DVI	1440*900	16,32	60,75
DVI	1400*1050	16,32	60
DVI	1680*1050	16,32	60
DVI	1600*1200	16,32	60
DVI	1792*1344	16,32	60
DVI	1800*1440	16,32	60
DVI	1856*1392	16,32	60
DVI	1920*1080	16,32	60
DVI	1920*1200	16,32	60
DVI	1920*1440	16,32	60

DVI	2048*1536	16,32	60
DVI	2560*1600	16,32	60
Y/Pb/Pr	720p	32	60
Y/Pb/Pr	1080i	32	30
TV	640*480	16,32	60
TV	720*480	16,32	60
TV	800*600	16,32	60
TV	1024*768	16,32	60

***Note:**

1. Test Operating System: Windows XP
2. Test Device: LCD Monitor
3. Tests results are based on the equipment of ASUS internal lab. Specifications are subject to change without notice.